

## **Specification Sheet**

Part Number: 596-00919



Metal Solar Placard, Hand Writable, PV AC DISCONNECT..., 3.75" x 1.0", AA, Black, 5/pkg

Article Number 596-00919

Type PVACDIS17M5

Color Black (BK)

Features & Benefits

 Placards made with UV stable inks and materials tested to last up to 25 years, even in direct sun exposure.
 Aggressive adhesive ensures strong bond, even on powder coated surfaces.
 Meets or exceeds NEC & IFC standards for printed text, character height, color and outdoor UV stability.
 Optional Paint Shields provide additional protection for pre-printed and variable data placards.

Quantity Per pack

_			_	_			
ם	rn	a	Inct	Des	2 C F I	nt	ınn
	ıv	u	uCL	DE	3 G I I	IJι	IUII

Variable data placards are used to mark areas specific to the individual installation, like voltage data. Made of the same durable material as pre-printed metal solar placards, HellermannTyton offers two styles of variable placards: hand-writable and engravable. Both hand-writable placards feature a silver variable data area that can be marked using an industrial paint pen. Engravable placards have a black area that can be engraved using standard engraving equipment.

**Short Description** 

Metal Solar Placard, Hand Writable, PV AC DISCONNECT..., 3.75" x 1.0", AA, Black, 5/pkg

**Global Part Name** 

PVACDIS17M5-AA-BK

**Technical Description** 

3.75" X 1" Silver aluminum text on black background that reads as: "PHOTOVOLTAIC AC DISCONNECT. RATED AC OUTPUT CURRENT. NOMINAL OPERATING AC VOLTAGE." 5 per pack. Nameplate is also printable using a paint pen to add the variable voltage information on demand.

Length L (Imperial)

1.0

Length L (Metric)

25.4

Width W (Imperial)

3.75

Width W (Metric)

95.25

Thickness T (Metric)

64.0

Height H (Imperial)

1.0

Height H (Metric)

25.40

Material

Anodized Aluminum (AA)

**Material Shortcut** 

AA

Adhesive

Ultra High Bond Permanent Acrylic Adhesive

Halogen free

No

**Adhesive Operating Temperature** 

from +50°F (from +10°C)

**Operating Temperature (Metric)** 

-40°F to +203°F (-40°C to +95°C)

Reach Complaint(Article 33)

Yes

**ROHS Complaint** 

Yes

**Certification/Specification WEB** 

NEC2017

Warranty (US)

Yes

Package Quantity(Imperial)

5

**Package Quantity (Metric)** 

5

**Customs Number** 

3919102055

Labels per Column

1

Labels per Row

1

Weight (Metric) .104
Weight (Imperial) 0.23

© 2020 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions