# Specification Sheet

Part Number: CTM210M4

Cable Tie Anchor Mount, .86" x .61", .18" Hole Dia, .31" Max Tie Width, PA66, White, 1000/pkg

| | |
|---|---|
| **Article Number** | 151-30506 |
| **Type** | CTM2 |
| **Color** | White (WH) |
| **Features & Benefits** | • Designed for use with 18 through 120 pound cable ties to provide stability when securing bundles. • Secures with a single screw providing quick installation. |
| **Quantity Per** | bag |
| **Product Description** | HellermannTyton cable tie mounts are designed for use with 18 through 120 pound cable ties to provide stability when securing bundles. The mounts are installed quick and easy by securing a single screw. |

| | |
|---|---|
| **Short Description** | Cable Tie Anchor Mount, .86" x .61", .18" Hole Dia, .31" Max Tie Width, PA66, White, 1000/pkg |
| **Global Part Name** | CTM2-PA66-WH |
| **Length L (Imperial)** | 0.86 |
| **Length L (Metric)** | 21.8 |
| **Fixation Method** | Screw Mounting and Rivet |
| **Width W (Imperial)** | 0.61 |
| **Width W (Metric)** | 15.5 |
| **Cable Ties** | T18 - T120 |
| **Height H (Imperial)** | .37 |
| **Height H (Metric)** | 9.40 |
| **Cable Tie Width Max (Imperial)** | 0.31 |
| **Cable Tie Width Max (Metric)** | 7.9 |
| **Mounting Hole Diameter D (Imperial)** | 0.18 |
| **Mounting Hole Diameter D (Metric)** | 4.6 mm |
| **Mounting Hole Diameter D Max (Metric)** | 4.6 |

| | |
|---|---|
| **Material** | Polyamide 6.6 (PA66) |
| **Material Shortcut** | PA66 |
| **Flammability** | UL 94 V2 |
| **Operating Temperature (Metric)** | -40°F to +185°F (-40°C to +85°C) |
| **ROHS Complaint** | Yes |
| **Certification/Specification WEB** | UL 62275 |
| **UL Recognized (US)** | Yes |
| **UL Recognized (US and Canada)** | Yes |
| **Package Quantity(Imperial)** | 1000 |
| **Package Quantity (Metric)** | 1000 |
| **Customs Number** | 3926909988 |

© 2020 HellermannTyton. All Rights Reserved.