

Specification Sheet

Part Number: CTT20R0HSC2



Clamp Tie, 4" Long, 20lb Tensile Strength, PA66HS, Black, 100/pkg

Article Number	112-51905
Type	CTT20R
Color	Black (BK)
Features & Benefits	• Head design contains clamping rails to provide full circumferential compression around bundles. • Bent tail allows for quick insertion into head.
Quantity Per	bag
Product Description	HellermannTyton clamp tie has triangular shaped tabs extending beneath the head for optimal surface contact and complete circumferential compression to 360 degrees. The bent tail design allows quick and simple installations by hand. The clamps are recommended for soft rubber hose applications including fuel, water, and air vaccuum lines.

Short Description	Clamp Tie, 4" Long, 20lb Tensile Strength, PA66HS, Black, 100/pkg
Global Part Name	CTT20R-PA66HS-BK
Minimum Tensile Strength (Imperial)	20.0
Minimum Tensile Strength (Metric)	90.0
Length L (Imperial)	4.0
Length L (Metric)	101.6
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.1
Width W (Metric)	2.5
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.6
Bundle Diameter Max (Imperial)	0.51
Bundle Diameter Max (Metric)	13.0

Thickness T (Imperial)	0.043
Thickness T (Metric)	1.1
Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL 94 V2
Operating Temperature (Metric)	-40°F to +257°F (-40°C to +125°C)
ROHS Complaint	Yes
Certification/Specification WEB	UL
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity(Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988
Content Unit(BMEcat)	pcs.

Weight (Metric) 0.0003

Weight (Imperial) 0.0007