

Specification Sheet

Part Number: DCT90HIRK2



Dual Clamp Tie, 13" Long, .25" Stud Dia, 1.30" Max Bundle Dia, 150lb, PA66HIRHSUV, Black 50/pkg

|                     |                                                                                                                                                                                                                                                                                                                                                      |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 115-30900                                                                                                                                                                                                                                                                                                                                            |
| Type                | DCT9                                                                                                                                                                                                                                                                                                                                                 |
| Color               | Black (BK)                                                                                                                                                                                                                                                                                                                                           |
| Features & Benefits | <ul style="list-style-type: none"><li>• Provides dual separation between bundles to prevent chafing and abrasion.</li><li>• 150lb. tensile strength ensures enough strength for heavy duty applications.</li><li>• Straps are releasable for increased serviceability.</li></ul>                                                                     |
| Quantity Per        | bag                                                                                                                                                                                                                                                                                                                                                  |
| Product Description | <p>Dual-Clamp Ties are designed to provide parallel separation between hoses, wires, cables, and tubing to protect them from abrasion. These ties have an optional mounting hole for securing bundles along the chassis of trucks, trailers, and heavy-duty equipment. The unique one-piece design features the dual head centered on the strap.</p> |

|                                            |                                                                                                 |
|--------------------------------------------|-------------------------------------------------------------------------------------------------|
| <b>Short Description</b>                   | Dual Clamp Tie, 13" Long, .25" Stud Dia, 1.30" Max Bundle Dia, 150lb, PA66HIRHSUV, Black 50/pkg |
| <b>Global Part Name</b>                    | DCT9-PA66HIRHSUV-BK                                                                             |
| <b>Minimum Tensile Strength (Imperial)</b> | 150.0                                                                                           |
| <b>Minimum Tensile Strength (Metric)</b>   | 667.0                                                                                           |
| <b>Length L (Imperial)</b>                 | 13.0                                                                                            |
| <b>Length L (Metric)</b>                   | 330.20                                                                                          |
| <b>Fixation Method</b>                     | Weld Stud Fixing                                                                                |
| <b>Identification Plate Position</b>       | none                                                                                            |
| <b>Releasable Closure</b>                  | No                                                                                              |
| <b>Tie Closure</b>                         | plastic pawl                                                                                    |
| <b>Variant</b>                             | Inside Serrated                                                                                 |
| <b>Width W (Imperial)</b>                  | 0.5                                                                                             |
| <b>Width W (Metric)</b>                    | 12.7                                                                                            |
| <b>Bundle Diameter Min (Imperial)</b>      | 0.25                                                                                            |
| <b>Bundle Diameter Min (Metric)</b>        | 6.4                                                                                             |

|                                       |                                                                          |
|---------------------------------------|--------------------------------------------------------------------------|
| <b>Bundle Diameter Max (Imperial)</b> | 1.3                                                                      |
| <b>Bundle Diameter Max (Metric)</b>   | 33.0                                                                     |
| <b>Height H (Imperial)</b>            | 0.8                                                                      |
| <b>Height H (Metric)</b>              | 20.32                                                                    |
| <b>Stud Diameter (Metric)</b>         | M6                                                                       |
| <b>Stud Diamater (Imperial)</b>       | 1/4                                                                      |
| <b>Material</b>                       | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| <b>Material Shortcut</b>              | PA66HIRHSUV                                                              |
| <b>Flammability</b>                   | UL 94 HB                                                                 |
| <b>Operating Temperature (Metric)</b> | -40°F to +221°F (-40°C to +105°C)                                        |
| <b>ROHS Complaint</b>                 | Yes                                                                      |
| <b>Package Quantity(Imperial)</b>     | 50                                                                       |
| <b>Package Quantity (Metric)</b>      | 50                                                                       |
| <b>Customs Number</b>                 | 3926909988                                                               |

|                             |     |
|-----------------------------|-----|
| <b>Content Unit(BMEcat)</b> | bag |
|-----------------------------|-----|

|                        |      |
|------------------------|------|
| <b>Weight (Metric)</b> | 12.0 |
|------------------------|------|

|                          |     |
|--------------------------|-----|
| <b>Weight (Imperial)</b> | 0.5 |
|--------------------------|-----|