

Specification Sheet

Part Number: ISO4X250H1



Isolator Mount for separating 0.25" Tubing, 0.25" Max Bundle Diameter, TPV, Black, 500/pkg

Article Number	151-00455
-----------------------	-----------

Type	ISO4X250
-------------	----------

Color	Black (BK)
--------------	------------

Features & Benefits	• Design provides quick and easy assembly. • Isolator mount dampens harmful vibrations on bundles • Material is durable, chemical and abrasion resistant, and remains flexible in low temperatures.
--------------------------------	---

Quantity Per	carton
---------------------	--------

Product Description	HellermannTyton's isolator mount is used to align and separate 1/4" tubing or brake lines. Easy to assemble, the isolator dampens vibrations and can be used with up to four brake lines. Mounting the isolator can be accomplished with HellermannTyton's standard cable ties, button head ties, and any of HellermannTyton's heavy equipment mounts. Mounting is optional, but recommended for long runs. The isolator is durable, chemical and abrasion resistant, and remains flexible in low temperatures.
Short Description	Isolator Mount for separating 0.25" Tubing, 0.25" Max Bundle Diameter, TPV, Black, 500/pkg
Global Part Name	ISO4X250-TPV-BK
Width W (Imperial)	0.92
Width W (Metric)	23.4
Height H (Imperial)	1.36
Height H (Metric)	34.5
Material	Thermoplastic vulcanized (TPV) rubber
Material Shortcut	TPV
Flammability	UL 94 HB
Operating Temperature (Metric)	-110°F to +347°F (-79°C to +175°C)
Reach Complaint(Article 33)	Yes

ROHS Complaint	Yes
-----------------------	-----

Package Quantity(Imperial)	500
-----------------------------------	-----

Package Quantity (Metric)	500
----------------------------------	-----

Customs Number	3926909988
-----------------------	------------

Content Unit(BMEcat)	pcs.
-----------------------------	------