


Specification Sheet

Part Number: MB4A10A2C2



Acrylic Adhesive Cable Tie Mount, 1.12" x 1.12", Use With T18-T50 Cable Tie, PA66, White, 100/pkg

Article Number	151-28420
Type	MB4A
Color	White (WH)
Features & Benefits	• For use with HellermannTyton T18 - T50 cable ties to provide stability when securing bundles. • 4-way opening allows cable ties to be installed parallel or perpendicular to bundles. • The rubber-based adhesive is an economical choice ideal for indoor applications, with a static load weight of 1.1 lb. • Two predrilled holes extend mounting options and solutions. • Extended adhesive liner is easy to remove quickly.
Quantity Per	bag

Product Description	MB4A adhesive mounts are for use with HellermannTyton T18 - T50 Series cable ties to provide stability when securing bundles. The rubber adhesive-backed mounts can be used to secure a bundle and have two predrilled holes to extend mounting options.
Short Description	Acrylic Adhesive Cable Tie Mount, 1.12" x 1.12", Use With T18-T50 Cable Tie, PA66, White, 100/pkg
Global Part Name	MB4A-PA66-WH
Length L (Imperial)	1.12
Length L (Metric)	28.5
Fixation Method	Screw Mounting and Adhesive
Width W (Imperial)	1.12
Width W (Metric)	28.5
Cable Ties	T18 - T50
Height H (Imperial)	.23
Height H (Metric)	5.8
Cable Tie Width Max (Imperial)	0.18
Cable Tie Width Max (Metric)	4.6
Mounting Hole Diameter D (Imperial)	0.18

Mounting Hole Diameter D (Metric) 4.6 mm

Mounting Hole Diameter D Max (Metric) 4.6

Mounting Hole Centers (Imperial) 0.8

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Adhesive Acrylate with base of acrylic foam

Flammability UL 94 V2 (excluding adhesive)

Adhesive Operating Temperature -31°F to +158°F (-35 °C to +70 °C)

Operating Temperature (Metric) -40°F to +185°F (-40°C to +85°C)

ROHS Complaint Yes

Package Quantity(Imperial) 100

Package Quantity (Metric) 100

Customs Number 3926909988

