

Specification Sheet

Part Number: MMB10H4



Masonry Cable Tie Mount, 1.712"L, .312" Hole Dia, .18" Max Cable Tie Width, PA66STHS, Black, 500/pkg

|                     |                                                                                                                                                                                                                                              |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 151-00327                                                                                                                                                                                                                                    |
| Type                | MMB1                                                                                                                                                                                                                                         |
| Color               | Black (BK)                                                                                                                                                                                                                                   |
| Features & Benefits | <ul style="list-style-type: none"><li>• Masonry Mounts provide a permanent solution when fastening wire and cables to masonry surfaces.</li><li>• The mounts have easy installation into predrilled holes allowing for faster use.</li></ul> |
| Quantity Per        | bag                                                                                                                                                                                                                                          |
| Product Description | HellermannTyton Masonry Mounts provide a permanent method of attaching wire and cable to masonry surfaces. Masonry mounts simply tap into predrilled holes and can be used for indoor and outdoor applications.                              |

|                                              |                                                                                                      |
|----------------------------------------------|------------------------------------------------------------------------------------------------------|
| <b>Short Description</b>                     | Masonry Cable Tie Mount, 1.712"L, .312" Hole Dia, .18" Max Cable Tie Width, PA66STHS, Black, 500/pkg |
| <b>Global Part Name</b>                      | MMB1-PA66STHS-BK                                                                                     |
| <b>Length L (Imperial)</b>                   | 1.712                                                                                                |
| <b>Length L (Metric)</b>                     | 43.5                                                                                                 |
| <b>Fixation Method</b>                       | with Fir Tree (Mounts)                                                                               |
| <b>Width W (Imperial)</b>                    | 0.508                                                                                                |
| <b>Width W (Metric)</b>                      | 12.9                                                                                                 |
| <b>Cable Ties</b>                            | T18 - T50                                                                                            |
| <b>Height H (Imperial)</b>                   | .50                                                                                                  |
| <b>Height H (Metric)</b>                     | 12.70                                                                                                |
| <b>Cable Tie Width Max (Imperial)</b>        | 0.18                                                                                                 |
| <b>Cable Tie Width Max (Metric)</b>          | 4.6                                                                                                  |
| <b>Mounting Hole Diameter D (Imperial)</b>   | 0.312                                                                                                |
| <b>Mounting Hole Diameter D (Metric)</b>     | 8.0 mm                                                                                               |
| <b>Mounting Hole Diameter D Max (Metric)</b> | 8.0                                                                                                  |

|                                       |                                                        |
|---------------------------------------|--------------------------------------------------------|
| <b>Material</b>                       | Polyamide 6.6, super tough, heat stabilized (PA66STHS) |
| <b>Material Shortcut</b>              | PA66STHS                                               |
| <b>Flammability</b>                   | UL 94 HB                                               |
| <b>Operating Temperature (Metric)</b> | -40°F to +221°F (-40°C to +105°C)                      |
| <b>ROHS Complaint</b>                 | Yes                                                    |
| <b>Package Quantity(Imperial)</b>     | 500                                                    |
| <b>Package Quantity (Metric)</b>      | 500                                                    |
| <b>Customs Number</b>                 | 3926909988                                             |