

Specification Sheet

Part Number: MMB.50C2



Masonry Cable Tie Mount, 1.24"L, .25" Hole Dia, .18" Max Cable Tie Width, PA66STHS, Black, 100/pkg

Article Number	151-00116
Type	MMB.5
Color	Black (BK)
Features & Benefits	• Masonry Mounts provide a permanent solution when fastening wire and cables to masonry surfaces. • The mounts have easy installation into predrilled holes allowing for faster use.
Quantity Per	bag
Product Description	HellermannTyton Masonry Mounts provide a permanent method of attaching wire and cable to masonry surfaces. Masonry mounts simply tap into predrilled holes and can be used for indoor and outdoor applications.

Short Description	Masonry Cable Tie Mount, 1.24"L, .25" Hole Dia, .18" Max Cable Tie Width, PA66STHS, Black, 100/pkg
Global Part Name	MMB.5-PA66STHS-BK
Length L (Imperial)	1.24
Length L (Metric)	31.5
Fixation Method	with Fir Tree (Mounts)
Width W (Imperial)	0.375
Width W (Metric)	9.5
Cable Ties	T18 - T50
Height H (Imperial)	.37
Height H (Metric)	9.40
Cable Tie Width Max (Imperial)	0.18
Cable Tie Width Max (Metric)	4.6
Mounting Hole Diameter D (Imperial)	0.25
Mounting Hole Diameter D (Metric)	6.35 mm
Mounting Hole Diameter D Max (Metric)	6.35

Material	Polyamide 6.6, super tough, heat stabilized (PA66STHS)
Material Shortcut	PA66STHS
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988
Content Unit(BMEcat)	pcs.