

Specification Sheet

Part Number: RT150LEP0X2



Releasable Cable Tie, Release Tab, 32.3" Long, 175lb Tensile Strength, PA66, Black, 25/pkg

|                     |                                                                                                                                                                                                                                                                                                                                                                     |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 115-00038                                                                                                                                                                                                                                                                                                                                                           |
| Type                | RT150LEP                                                                                                                                                                                                                                                                                                                                                            |
| Color               | Black (BK)                                                                                                                                                                                                                                                                                                                                                          |
| Features & Benefits | <ul style="list-style-type: none"><li>• Special design with extended pawl offers a release feature for quick and easy access to wire bundles.</li><li>• Head design provides high tensile strength with very low insertion force even after repeated use.</li></ul>                                                                                                 |
| Quantity Per        | bag                                                                                                                                                                                                                                                                                                                                                                 |
| Product Description | HellermannTyton Releasable Cable Ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high-volume applications, tensioning tools are available to ensure consistent and safe installation. |

|                                            |                                                                                            |
|--------------------------------------------|--------------------------------------------------------------------------------------------|
| <b>Short Description</b>                   | Releasable Cable Tie, Release Tab, 32.3" Long, 175lb Tensile Strength, PA66, Black, 25/pkg |
| <b>Global Part Name</b>                    | RT150LEP-PA66-BK                                                                           |
| <b>Minimum Tensile Strength (Imperial)</b> | 175.0                                                                                      |
| <b>Minimum Tensile Strength (Metric)</b>   | 780.0                                                                                      |
| <b>Length L (Imperial)</b>                 | 32.3                                                                                       |
| <b>Length L (Metric)</b>                   | 820.0                                                                                      |
| <b>Identification Plate Position</b>       | none                                                                                       |
| <b>Releasable Closure</b>                  | Yes                                                                                        |
| <b>Tie Closure</b>                         | plastic pawl                                                                               |
| <b>Variant</b>                             | Inside Serrated                                                                            |
| <b>Width W (Imperial)</b>                  | 0.35                                                                                       |
| <b>Width W (Metric)</b>                    | 8.8                                                                                        |
| <b>Bundle Diameter Min (Imperial)</b>      | 0.31                                                                                       |
| <b>Bundle Diameter Min (Metric)</b>        | 8.0                                                                                        |
| <b>Bundle Diameter Max (Imperial)</b>      | 9.65                                                                                       |

|                                       |                                  |
|---------------------------------------|----------------------------------|
| <b>Bundle Diameter Max (Metric)</b>   | 245.0                            |
| <b>Cable Tie Width Max (Imperial)</b> | 0.346                            |
| <b>Cable Tie Width Max (Metric)</b>   | 8.8                              |
| <b>Material</b>                       | Polyamide 6.6 (PA66)             |
| <b>Material Shortcut</b>              | PA66                             |
| <b>Flammability</b>                   | UL 94 V2                         |
| <b>Operating Temperature (Metric)</b> | -40°F to +185°F (-40°C to +85°C) |
| <b>ROHS Complaint</b>                 | Yes                              |
| <b>Package Quantity(Imperial)</b>     | 25                               |
| <b>Package Quantity (Metric)</b>      | 25                               |
| <b>Customs Number</b>                 | 3926909988                       |