

Specification Sheet

Part Number: RT250I0UVX2



Releasable Cable Tie, Release Tab, 28.7" Long, 250lb Tensile Strength, PA66UV, Black, 25/pkg

Article Number	115-41403
Type	RT250I
Color	Black (BK)
Features & Benefits	• Special extended-pawl design offers a release feature for quick and easy access to wire bundles. • Head design provides high tensile strength with very low insertion force even after repeated use. • Buckle feature on head allows excess strap to be tucked away after installation.
Quantity Per	bag

Product Description	HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force . For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Releasable Cable Tie, Release Tab, 28.7" Long, 250lb Tensile Strength, PA66UV, Black, 25/pkg
Global Part Name	RT250I-PA66UV-BK
Minimum Tensile Strength (Imperial)	250.0
Minimum Tensile Strength (Metric)	1115.0
Length L (Imperial)	28.7
Length L (Metric)	730.0
Identification Plate Position	none
Releasable Closure	Yes
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.49
Width W (Metric)	12.5
Bundle Diameter Min (Imperial)	0.47

Bundle Diameter Min (Metric)	12.0
Bundle Diameter Max (Imperial)	8.0
Bundle Diameter Max (Metric)	203.0
Thickness T (Imperial)	0.0837
Thickness T (Metric)	2.2
Cable Tie Head Length (Imperial)	0.88
Cable Tie Head Width (Imperial)	0.79
Material	Polyamide 6.6 UV-stabilized (PA66UV)
Material Shortcut	PA66UV
Flammability	UL 94 V2
Operating Temperature (Metric)	-40°F to +185°F (-40°C to +85°C)
ROHS Complaint	Yes
Certification/Specification WEB	UL
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes

Package Quantity(Imperial)	25
Package Quantity (Metric)	25
Customs Number	3926909988
Content Unit(BMEcat)	pcs.