

Specification Sheet

Part Number: RT250S0UVX2



Releasable Cable Tie, Release Tab, 9.1" Long, 250lb Tensile Strength, PA66UV, Black, 25/pkg

Article Number	115-41803
Type	RT250S
Color	Black (BK)
Features & Benefits	• Special extended-pawl design offers a release feature for quick and easy access to wire bundles. • Head design provides high tensile strength with very low insertion force even after repeated use. • Buckle feature on head allows excess strap to be tucked away after installation.
Quantity Per	bag

Product Description	HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force . For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Releasable Cable Tie, Release Tab, 9.1" Long, 250lb Tensile Strength, PA66UV, Black, 25/pkg
Global Part Name	RT250S-PA66W-BK
Minimum Tensile Strength (Imperial)	250.0
Minimum Tensile Strength (Metric)	1115.0
Length L (Imperial)	9.1
Length L (Metric)	230.0
Identification Plate Position	none
Releasable Closure	Yes
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.49
Width W (Metric)	12.5
Bundle Diameter Min (Imperial)	0.47

Bundle Diameter Min (Metric)	12.0
Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0
Thickness T (Imperial)	0.075
Thickness T (Metric)	1.9
Cable Tie Head Length (Imperial)	0.88
Cable Tie Head Width (Imperial)	0.79
Material	Polyamide 6.6 UV-resistant (PA66UV)
Material Shortcut	PA66W
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +185°F (-40°C to +85°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	UL
UL Recognized (US)	Yes

UL Recognized (US and Canada)	Yes
--------------------------------------	-----

Package Quantity(Imperial)	25
-----------------------------------	----

Package Quantity (Metric)	25
----------------------------------	----

Customs Number	3926909988
-----------------------	------------

Content Unit(BMEcat)	pcs.
-----------------------------	------