HellermannTyton

Specification Sheet

Part Number: SNP1.510M4



Snapper Hose Clamp, .31"-.35" Bundle Diameter, POM, White, 1000/pkg

Article Number 190-00034

Type SNP1.5

Color White (WH)

Features & Benefits • Designed for quick, ratcheted installation and can be released and

reused. • Polyacetal material resists chemicals, corrosion and UV

rays making it suitable for extreme environments.

Quantity Per bag

_		_		4 .
Proc	れいたも	Desc	rın	tınn
1100	uuu	D C30	110	uvii

Snapper Hose Clamps are lightweight and corrosion-resistant. Manufactured from high-performance thermoplastic materials selected to work well in a variety of diverse environments. A quick ratchet closure provides for reduced assembly line time and allows for application after connection of the hose. Release is achieved by initiating opposed lateral movement of the ratchet ends. Heat stabilized materials are available for high-temperature, motor, and under-hood applications. Snappers are also stable in a wide variety of chemicals including salts, bases, alcohols, ethers, detergents, gasoline, lubricating oils, and greases. The Snapper is available in 32 standard sizes ranging from 1/4" to 4-1/2" ID. Snappers are manufactured in white polyacetal and black polyamide 6.6 glass filled impact modified heat stabilized material. Custom designed and different colored or shaped Snappers are available based upon applications and volume requirements.

Short Description

Snapper Hose Clamp, .31"-.35" Bundle Diameter, POM, White,

1000/pkg

Global Part Name

SNP1.5-POM-WH

Fixation Method

Plug-in mounting

Variant

Closed

Wall Thickness WT (Imperial)

.054

Wall Thickness WT (Metric)

1.4

Material

Polyacetal (POM)

Material Shortcut

POM

Flammability UL 94 HB

UV Resistant (Yes/No) No

Operating Temperature (Metric) -40°F to +194°F (-40°C to +90°C)

ROHS Complaint Yes

Package Quantity(Imperial) 1000

Package Quantity (Metric) 1000

Customs Number 3926909988

Weight (Metric) 0.5

© 2020 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions