

Specification Sheet

Part Number: T150L0K2



Heavy Duty Cable Tie, 32" Long, UL Rated, 175lb Tensile Strength, PA66, Black, 50/pkg

|                     |                                                                                                                                                                                                                                                                                                                                  |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 111-15404                                                                                                                                                                                                                                                                                                                        |
| Type                | T150L                                                                                                                                                                                                                                                                                                                            |
| Color               | Black (BK)                                                                                                                                                                                                                                                                                                                       |
| Features & Benefits | <ul style="list-style-type: none"><li>• Engineered and manufactured for maximum performance and quality.</li><li>• Made from 100% high-quality plastic to ensure efficient recycling.</li><li>• Inside serration for a strong grip onto bundles.</li><li>• Easy application either manually or with a tensioning tool.</li></ul> |
| Quantity Per        | bag                                                                                                                                                                                                                                                                                                                              |
| Product Description | Heavy duty T-Series cable ties feature inside serrations to provide a positive hold on wire and cable bundles. Durable head design guarantees high tensile strength and a low insertion force. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.                          |

|                                            |                                                                                       |
|--------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Short Description</b>                   | Heavy Duty Cable Tie, 32" Long, UL Rated, 175lb Tensile Strength, PA66, Black, 50/pkg |
| <b>Global Part Name</b>                    | T150L-PA66-BK                                                                         |
| <b>Minimum Tensile Strength (Imperial)</b> | 175.0                                                                                 |
| <b>Minimum Tensile Strength (Metric)</b>   | 780.0                                                                                 |
| <b>Length L (Imperial)</b>                 | 32.0                                                                                  |
| <b>Length L (Metric)</b>                   | 820.0                                                                                 |
| <b>Identification Plate Position</b>       | none                                                                                  |
| <b>Releasable Closure</b>                  | No                                                                                    |
| <b>Tie Closure</b>                         | plastic pawl                                                                          |
| <b>Variant</b>                             | Inside Serrated                                                                       |
| <b>Width W (Imperial)</b>                  | 0.35                                                                                  |
| <b>Width W (Metric)</b>                    | 8.9                                                                                   |
| <b>Bundle Diameter Min (Imperial)</b>      | 0.31                                                                                  |
| <b>Bundle Diameter Min (Metric)</b>        | 8.0                                                                                   |
| <b>Bundle Diameter Max (Imperial)</b>      | 9.65                                                                                  |

|                                        |                                  |
|----------------------------------------|----------------------------------|
| <b>Bundle Diameter Max (Metric)</b>    | 245.0                            |
| <b>Thickness T (Metric)</b>            | 1.9                              |
| <b>Material</b>                        | Polyamide 6.6 (PA66)             |
| <b>Material Shortcut</b>               | PA66                             |
| <b>Flammability</b>                    | UL 94 V2                         |
| <b>Halogen free</b>                    | Yes                              |
| <b>Operating Temperature (Metric)</b>  | -40°F to +185°F (-40°C to +85°C) |
| <b>ROHS Complaint</b>                  | Yes                              |
| <b>Certification/Specification WEB</b> | UL-ZODZ2.E64139                  |
| <b>UL Recognized (US)</b>              | Yes                              |
| <b>UL Recognized (US and Canada)</b>   | Yes                              |
| <b>Package Quantity(Imperial)</b>      | 50                               |
| <b>Package Quantity (Metric)</b>       | 50                               |
| <b>Customs Number</b>                  | 3926909988                       |

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)