

Specification Sheet

Part Number: T18MR0M4



1-Piece Cable Tie/Screw Mount, 4.3" Long, #4 Screw, .79" Max Bundle Dia, 18lb, PA66, Black, 1000/pkg

|                     |                                                                                                                                                                                                                          |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 113-00024                                                                                                                                                                                                                |
| Type                | T18MR                                                                                                                                                                                                                    |
| Color               | Black (BK)                                                                                                                                                                                                               |
| Features & Benefits | <ul style="list-style-type: none"><li>• Screw mount style creates low insertion and high extraction force.</li><li>• Choose from several tensile strengths and lengths to accommodate a range of applications.</li></ul> |
| Quantity Per        | bag                                                                                                                                                                                                                      |
| Product Description | One-piece Screw Mount Cable Ties fasten with a screw or bolt to provide secure routing of cable bundles. Multiple configurations are available to cover a range of bundle sizes and tensile strengths.                   |

|                                            |                                                                                                      |
|--------------------------------------------|------------------------------------------------------------------------------------------------------|
| <b>Short Description</b>                   | 1-Piece Cable Tie/Screw Mount, 4.3" Long, #4 Screw, .79" Max Bundle Dia, 18lb, PA66, Black, 1000/pkg |
| <b>Global Part Name</b>                    | T18MR-PA66-BK                                                                                        |
| <b>Minimum Tensile Strength (Imperial)</b> | 18.0                                                                                                 |
| <b>Minimum Tensile Strength (Metric)</b>   | 80                                                                                                   |
| <b>Length L (Imperial)</b>                 | 4.3                                                                                                  |
| <b>Length L (Metric)</b>                   | 110.0                                                                                                |
| <b>Fixation Method</b>                     | Fixing hole                                                                                          |
| <b>Identification Plate Position</b>       | none                                                                                                 |
| <b>Releasable Closure</b>                  | No                                                                                                   |
| <b>Tie Closure</b>                         | plastic pawl                                                                                         |
| <b>Variant</b>                             | Inside Serrated                                                                                      |
| <b>Width W (Imperial)</b>                  | 0.1                                                                                                  |
| <b>Width W (Metric)</b>                    | 2.5                                                                                                  |
| <b>Bundle Diameter Min (Imperial)</b>      | 0.06                                                                                                 |
| <b>Bundle Diameter Min (Metric)</b>        | 1.5                                                                                                  |

|                                              |        |
|----------------------------------------------|--------|
| <b>Bundle Diameter Max (Imperial)</b>        | 0.8    |
| <b>Bundle Diameter Max (Metric)</b>          | 20.0   |
| <b>Thickness T (Imperial)</b>                | 0.039  |
| <b>Thickness T (Metric)</b>                  | 1.0    |
| <b>Height H (Imperial)</b>                   | .17    |
| <b>Height H (Metric)</b>                     | 4.20   |
| <b>Mounting Hole Diameter D (Imperial)</b>   | 0.12   |
| <b>Mounting Hole Diameter D (Metric)</b>     | 3.1 mm |
| <b>Mounting Hole Diameter D Max (Metric)</b> | 3.1    |

|                                        |                                   |
|----------------------------------------|-----------------------------------|
| <b>Material</b>                        | Polyamide 6.6 (PA66)              |
| <b>Material Shortcut</b>               | PA66                              |
| <b>Flammability</b>                    | UL 94 V2                          |
| <b>Operating Temperature (Metric)</b>  | -40°F to +221°F (-40°C to +105°C) |
| <b>ROHS Complaint</b>                  | Yes                               |
| <b>Certification/Specification WEB</b> | UL                                |

|                           |     |
|---------------------------|-----|
| <b>UL Recognized (US)</b> | Yes |
|---------------------------|-----|

|                                      |     |
|--------------------------------------|-----|
| <b>UL Recognized (US and Canada)</b> | Yes |
|--------------------------------------|-----|

|                                   |      |
|-----------------------------------|------|
| <b>Package Quantity(Imperial)</b> | 1000 |
|-----------------------------------|------|

|                                  |      |
|----------------------------------|------|
| <b>Package Quantity (Metric)</b> | 1000 |
|----------------------------------|------|

|                       |            |
|-----------------------|------------|
| <b>Customs Number</b> | 3926909988 |
|-----------------------|------------|