

Specification Sheet

Part Number: T18R2HALC2



High-Temp Cable Tie, 4" Long, 14lb Tensile Strength, E/CTFE, Red, 100/pkg

Article Number	111-01900
Type	T18R
Color	Red (RD)
Features & Benefits	• Halar cable ties feature a UL 94 V-0 rating to comply with low flame and smoke requirements. • Inside serrations provide strong grip on cables and wire bundles. • Easy application either manually or with a tensioning tool. • Bent tail ensures a quick and simple installation.
Quantity Per	bag

Product Description	The raw material used to manufacture HellermannTyton Halar cable ties is UL 94 V-0 rated. The Halar ties come in a distinct red color for easy identification. T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	High-Temp Cable Tie, 4" Long, 14lb Tensile Strength, E/CTFE, Red, 100/pkg
Global Part Name	T18R-E/CTFE-RD
Minimum Tensile Strength (Imperial)	14.0
Minimum Tensile Strength (Metric)	62.0
Length L (Imperial)	4.0
Length L (Metric)	100.0
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.10
Width W (Metric)	2.5

Bundle Diameter Min (Imperial) 0.19

Bundle Diameter Min (Metric) 4.8

Bundle Diameter Max (Imperial) 0.87

Bundle Diameter Max (Metric) 22.0

Thickness T (Metric) 1.0

Height H (Metric) 3.7

Material Ethylene Chlorotrifluoroethylene (E/CTFE)

Material Shortcut E/CTFE

Flammability UL 94 V0

Operating Temperature (Metric) -103°F to +302°F (-75°C to +150°C)

ROHS Complaint Yes

Package Quantity(Imperial) 100

Package Quantity (Metric) 100

Customs Number 3926909988

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)