

Specification Sheet

Part Number: T30RSF0M4



1-Piece Cable Tie/Arrowhead Mount, 6.3"L, 30lb, 0.04"–0.09" Panel Thickness, PA66HS, Black, 1000/pkg

Article Number	126-00702
Type	T30RSF(U)
Color	Black (BK)
Features & Benefits	• All-in-one bundling and fastening solution reduces costs and assembly time. • The arrowhead design of these ties offers a low insertion force and a high extraction force. • High-spec materials and superior design deliver versatility, performance and value.
Quantity Per	bag

Product Description	One-piece mounting ties offer a complete solution by both bundling cable and simultaneously providing a mounting solution. The arrowhead design of this push mount inserts easily and locks securely in place. HellermannTyton's one-piece mounting ties combine high-specification materials with superior design to deliver dependable performance in a range of applications.
Short Description	1-Piece Cable Tie/Arrowhead Mount, 6.3"L, 30lb, 0.04"–0.09" Panel Thickness, PA66HS, Black, 1000/pkg
Global Part Name	T30RSF(U)-PA66HS-BK
Minimum Tensile Strength (Imperial)	30.0
Minimum Tensile Strength (Metric)	135
Length L (Imperial)	6.3
Length L (Metric)	160.02
Fixation Method	Arrowhead
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.14
Width W (Metric)	3.6

Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.6
Bundle Diameter Max (Imperial)	1.3
Bundle Diameter Max (Metric)	31.0
Thickness T (Imperial)	0.05
Thickness T (Metric)	1.2
Height H (Imperial)	.20
Height H (Metric)	5.70
Panel Thickness Min(Imperial)	0.035
Panel Thickness Max(Imperial)	0.094
Panel Thickness Min (Metric)	0.9
Panel Thickness Max (Metric)	2.4
Mounting Hole Diameter D (Imperial)	0.19 - 0.22
Mounting Hole Diameter D (Metric)	4.7 - 5.6 mm
Mounting Hole Diameter D Min (Imperial)	0.19
Mounting Hole Diameter D Max (Imperial)	0.22
Mounting Hole Diameter D Max (Metric)	5.6

Material	Polyamide 6.6 heat stabilized (PA66HS)
-----------------	--

Material Shortcut	PA66HS
--------------------------	--------

Flammability	UL 94 V2
---------------------	----------

Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
---------------------------------------	-----------------------------------

ROHS Complaint	Yes
-----------------------	-----

Certification/Specification WEB	UL-ZODZ2.E64139
--	-----------------

UL Recognized (US)	Yes
---------------------------	-----

UL Recognized (US and Canada)	Yes
--------------------------------------	-----

Package Quantity(Imperial)	1000
-----------------------------------	------

Package Quantity (Metric)	1000
----------------------------------	------

Customs Number	3926909988
-----------------------	------------