

Specification Sheet

Part Number: T50RDH9M4



Double-Head Cable Tie, 8.3" Long, 50lb Tensile Strength, PA66, Natural, 1000/pkg

Article Number	117-05008
Type	T50RDH
Color	Natural (NA)
Features & Benefits	• The tie contains a dual locking design to secure two bundles at once. • Head design can also provide spacing between parallel bundles. • Bent tail allows for quick insertion into head.
Quantity Per	bag
Product Description	The double head cable tie was designed with a dual locking head that creates two loops to secure two bundles simultaneously. The head also provides separation between bundles or bundles running parallel to each other. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description	Double-Head Cable Tie, 8.3" Long, 50lb Tensile Strength, PA66, Natural, 1000/pkg
Global Part Name	T50RDH-PA66-NA
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225.0
Length L (Imperial)	8.3
Length L (Metric)	210.82
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.19
Width W (Metric)	4.7
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.6
Bundle Diameter Max (Imperial)	1.5

Bundle Diameter Max (Metric)	38.0
-------------------------------------	------

Bundle Diameter 1st Loop Max (Imperial)	1.7
--	-----

Bundle Diameter 1st Loop Max (Metric)	44.4
--	------

Bundle Diameter 2nd Loop Max (Imperial)	0.75
--	------

Bundle Diameter 2nd Loop Max (Metric)	19.0
--	------

Material	Polyamide 6.6 (PA66)
-----------------	----------------------

Material Shortcut	PA66
--------------------------	------

Flammability	UL 94 V2
---------------------	----------

Halogen free	Yes
---------------------	-----

Operating Temperature (Metric)	-40°F to +185°F (-40°C to +85°C)
---------------------------------------	----------------------------------

ROHS Complaint	Yes
-----------------------	-----

Certification/Specification WEB	UL
--	----

UL Recognized (US)	Yes
---------------------------	-----

UL Recognized (US and Canada)	Yes
--------------------------------------	-----

Package Quantity(Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988