

Specification Sheet

Part Number: TELS-SPK2



Extended-Length Tie Spacer, PP, Black, 50/pkg

|                     |                                                                                                                                                                                                                                                                                                                                                                 |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 111-32000                                                                                                                                                                                                                                                                                                                                                       |
| Type                | EL-TY (TELS-SPK2)                                                                                                                                                                                                                                                                                                                                               |
| Color               | Black (BK)                                                                                                                                                                                                                                                                                                                                                      |
| Features & Benefits | <ul style="list-style-type: none"><li>• Spacers provide distance between two bundles.</li><li>• Continuous strap and separate heads allow for any bundle diameter, eliminating waste.</li><li>• Smooth strap prevents cable damage.</li><li>• UV resistant materials contain an inhibitor which prolongs the life of the tie in outdoor environments.</li></ul> |
| Quantity Per        | bag                                                                                                                                                                                                                                                                                                                                                             |

|                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|--------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product Description</b>                 | Extended Length Ties provide a high tensile strength strapping system consisting of a continuous strap and separate locking head making it suitable for any bundle diameter, eliminating waste. The smooth strap and specially designed heads with stainless steel pawls provide a strong grip on cables and wires without damage during vibration or in extreme environments. Spacers are available for dual bundle applications. |
| <b>Short Description</b>                   | Extended-Length Tie Spacer, PP, Black, 50/pkg                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Global Part Name</b>                    | EL-TY (TELS-SPK2)-PP-BK                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Contents of pkg/kit</b>                 | 50 Spacer                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Minimum Tensile Strength (Imperial)</b> | 250.0                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Minimum Tensile Strength (Metric)</b>   | 1115.0                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Length L (Imperial)</b>                 | 1.2                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Length L (Metric)</b>                   | 30.5                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Fixation Method</b>                     | 2 piece                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Identification Plate Position</b>       | none                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Releasable Closure</b>                  | No                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Tie Closure</b>                         | steel pawl                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Variant</b>                             | Extended Length                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Width W (Imperial)</b>                  | 2.1                                                                                                                                                                                                                                                                                                                                                                                                                                |

|                                       |                                                                  |
|---------------------------------------|------------------------------------------------------------------|
| <b>Width W (Metric)</b>               | 53.3                                                             |
| <b>Height H (Imperial)</b>            | 0.67                                                             |
| <b>Height H (Metric)</b>              | 17.0                                                             |
| <b>Cable Tie Width Max (Metric)</b>   | 12.7                                                             |
| <b>Material</b>                       | Polypropylene (PP)                                               |
| <b>Material Shortcut</b>              | PP                                                               |
| <b>Material Head</b>                  | Polyacetal, UV stabilized (POMUV) with stainless steel pawl (SS) |
| <b>Flammability</b>                   | UL 94 HB                                                         |
| <b>Operating Temperature (Metric)</b> | -40°F to +239°F (-40°C to +115°C)                                |
| <b>Reach Complaint(Article 33)</b>    | Yes                                                              |
| <b>ROHS Complaint</b>                 | Yes                                                              |
| <b>Package Quantity(Imperial)</b>     | 50                                                               |
| <b>Package Quantity (Metric)</b>      | 50                                                               |
| <b>Customs Number</b>                 | 3926909988                                                       |

**Content Unit(BMEcat)** pcs.

**Weight (Metric)** 0.6