## **HellermannTyton**

## **Specification Sheet**

Part Number: TSR3I-36



End Cap, 1-3/4", 2-Piece, PVC, Ivory, 10 Individual/bag

| Article Number      | 250-03361   |
|---------------------|---|
| Туре                | TSR3-36   |
| Color               | Ivory (IV)  |
| Features & Benefits | • Tamper resistant covers with hidden latch provide security while<br>allowing quick entry for cable maintenance. • PVC construction is<br>lightweight, durable and more affordable than metallic raceway<br>systems. • Flexible hinge is designed to reduce stress cracking and<br>discoloration from repeated opening and closing. • Systems and<br>fittings are available in white, office white and ivory to coordinate with<br>a variety of décor. • Fittings incorporate a minimum 1" bend radius to<br>meet TIA/EIA 568-B and 569-A standards. |
| Quantity Per        | bag   |

| Product Description            | HellermannTyton surface raceway systems are the ideal solution for<br>routing communication and power cables. No need to break into<br>existing walls - raceway systems are designed to route cable along<br>wall surfaces. Made of a PVC material, components are durable and<br>affordable; and the one-piece construction and adhesive tape backing<br>make positioning and mounting easy. HellermannTyton offers a low<br>voltage TSR system and a power rated TSRP system that are<br>available in three different diameters to accommodate different cable<br>and wire bundle and conduit sizes. Both systems include a complete<br>line of fittings and junction boxes that allow for clean and professional<br>installations. TSR surface raceway systems can be used to route a<br>variety of communication cable, including high speed UTP and fiber<br>optic cable. |
|--------------------------------|--|
| Short Description              | End Cap, 1-3/4", 2-Piece, PVC, Ivory, 10 Individual/bag  |
| Global Part Name               | TSR3-36-PVC-BGE  |
| Material                       | Polyvinylchloride (PVC)  |
| Material Shortcut              | PVC  |
| Flammability                   | UL 94 V0   |
| Halogen free                   | No   |
| Operating Temperature (Metric) | +122°F (+50°C)   |
| Reach Complaint(Article 33)    | No   |
| ROHS Complaint                 | Yes  |
|                                |  |

Package Quantity(Imperial) 10

**Customs Number** 

3925900000

10

© 2020 HellermannTyton. All Rights Reserved. Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions