

Specification Sheet

Part Number: TSRP3FW-36



End Cap, 1-3/4", 3-Piece, PVC, Office White, 10 Individual/bag

Article Number	250-63360
Type	TSRP3-36
Color	Office White (OEWH)
Features & Benefits	<ul style="list-style-type: none"><li>• Tamper resistant covers with hidden latch provide security while allowing quick entry for cable maintenance.</li><li>• PVC construction is lightweight, durable and more affordable than metallic raceway systems.</li><li>• Flexible hinge designed to reduce stress cracking and discoloration from repeated opening and closing.</li><li>• Systems and fittings are available in white, office white and ivory to coordinate with a variety of décor.</li><li>• Fittings incorporate a minimum 1” bend radius to meet TIA/EIA 568-B and 569-A standards.</li><li>• TSRP power rated surface raceway systems have an enhanced “channel and lug” mating design that provides a tighter, more secure fit between raceway lengths and fittings, enabling the system to be UL Listed for power up to 600 volts and meet UL5A and CSA 22.2.</li></ul>
Quantity Per	EA

<b>Product Description</b>	HellermannTyton surface raceway systems are the ideal solution for routing communication and power cables. No need to break into existing walls - raceway systems are designed to route cable along wall surfaces. Made of a PVC material, components are durable and affordable; and the one piece construction and adhesive tape backing make positioning and mounting easy. HellermannTyton offers a low voltage TSR system and a power rated TSRP system that are available in three different diameters to accommodate different cable and wire bundle and conduit sizes. Both systems include a complete line of fittings and junction boxes that allow for clean and professional installations. TSRP surface raceway systems are designed to aesthetically organize and route either power or communications cables.
<b>Short Description</b>	End Cap, 1-3/4", 3-Piece, PVC, Office White, 10 Individual/bag
<b>Global Part Name</b>	TSRP3-36-PVC-WH
<b>Material</b>	Polyvinylchloride (PVC)
<b>Material Shortcut</b>	PVC
<b>Flammability</b>	UL 94 V0
<b>Halogen free</b>	No
<b>Operating Temperature (Metric)</b>	+122°F (+50°C)
<b>Reach Complaint(Article 33)</b>	No
<b>ROHS Complaint</b>	Yes
<b>UL Listed (US and Canada)</b>	Yes
<b>UL Listed (US</b>	Yes

<b>Package Quantity(Imperial)</b>	10
<b>Package Quantity (Metric)</b>	10
<b>Customs Number</b>	3925900000