APPLICA	BLE STAN	DARD									
OPERATING TEMPERATURE RANG		E RANGE	-35°C TO +85°C (NOTES 1)		TEMF	STORAGE TEMPERATURE RANGE			−10°C TO +60°C		
RATING	G VOLTAGE		30V AC		1	ICABLE NECTOR			BM10* (**) -*DS-0. 4V (**)		*)
	CURRENT		0. 3A								
SPECIFICATIONS											
ITEM			TEST METHOD				R	REQU	IREMENTS	QT	АТ
	RUCTION										
INST			NFIRMED VISUALLY AND BY MEASURING STRUMENT.			ACCOF	RDING T	O DR	AWING.	X	X
MARKING			CONFIRMED VISUALLY.							X	X
		CTERISTICS									
CONTACT	RESISTANCE	20mV AC OR LESS 1khz,1m A .				200mΩ MAX.					-
INSULATION RESISTANCE		100V DC.				50M Ω MIN .				Х	-
VOLTAGE PROOF		100V AC FOR 1 min.				NO FLASHOVER OR BREAKDOWN.				Х	_
MECHANICAL CHARACTERISTICS											1
MECHANIC, OPERATION	AL .	500TIMES INSERTIONS AND EXTRACTIONS.			·	① CONTACT RESISTANCE: 200mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.				X	_
COUN	II DE	-SCRIPTI	ON OF REVISIONS		DESIG	NED			CHECKED	DA	TE
REMARKS NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT Unless otherwise specified, refer to JIS C 5402 and IEC 60512							APPRO' CHECK DESIGN	(ED NED	KH. IKEDA KY. MIDORIKAWA NY. YAMASHIRO SH. HOSODA		
					DF	RAWING NO. ELC4-32136			-53		
RS SPECIFICATION SHEET PART							BM10JC-*DP-0. 4V (53)				
	HIROSE ELECTRIC CO., LTD. COD					NO.	CL684 🛆 1/				1/