




| | | | | | |
|---|-----------------------------|--|--|----------------------------|--|
| APPLICABLE STANDARD | | | | | |
| RATING | OPERATING TEMPERATURE RANGE | -35°C TO +85°C (NOTES 1) | STORAGE TEMPERATURE RANGE | -10°C TO +60°C | |
| | VOLTAGE | 30V AC | APPLICABLE CONNECTOR | DF36A-25S-0.4V | |
| | CURRENT | 0.25A | APPLICABLE CABLE | THIN COAXIAL CABLE(AWG#42) | |
| SPECIFICATIONS | | | | | |
| ITEM | | TEST METHOD | REQUIREMENTS | QT | AT |
| CONSTRUCTION | | | | | |
| GENERAL EXAMINATION | | VISUALLY AND BY MEASURING INSTRUMENT. | ACCORDING TO DRAWING. | X | X |
| MARKING | | CONFIRMED VISUALLY. | | X | X |
| ENVIRONMENTAL CHARACTERISTICS | | | | | |
| SALT MIST | | EXPOSED IN 5 % SALT WATER SPRAY 48 h. | NO DEFECT SUCH AS CORROSION WHICH IMPAIRS THE FUNCTION OF CONNECTOR. | X | — |
| SULFUR DIOXIDE GAS | | EXPOSED IN 10-15 PPM 96h. | | X | — |
| RESISTANCE TO SOLDERING HEAT | | ① BONDING TEMPERATURE: 270°C MAX :5 sec MAX 200°C MIN :30 sec MAX ② MANUAL SOLDERING TEMPERATURE: 350°C, 3sec MAX. | NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS. | X | — |
| SOLDERABILITY | | SOLDERED AT SOLDER TEMPERATURE, 230°C FOR INSERTION DURATION, 3 sec. | SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMersed. | X | — |
| | | | | | |
| | COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE |
|  | | | | | |
| REMARKS NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT Unless otherwise specified, refer to JIS C 5402, IEC60512. | | | APPROVED | TY. OMA | 07. 01. 11 |
| | | | CHECKED | TS. SAKATA | 07. 01. 11 |
| | | | DESIGNED | MN. KENJO | 07. 01. 09 |
| | | | DRAWN | MN. KENJO | 07. 01. 09 |
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test | | | DRAWING NO. | | ELC4-312854-00 |
|  | SPECIFICATION SHEET | | PART NO. | DF36A-25P-SHL | |
| | HIROSE ELECTRIC CO., LTD. | | CODE NO. | CL662-4007-7-00 |  1/ |