

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C	
	OPERATING&STORAGE HUMIDTY RANGE	85%MAX	APPLICABLE CABLE	CABLE DIAMETER : ϕ 8.3~9.3	
	VOLTAGE		CURRENT		
SPECIFICATIONS					
ITEM	TEST METHOD		REQUIREMENTS	QT	AT
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.			X	X
COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
2	DIS-E-00002570		TS. ITO	TU. TANIGUCHI	20191007
REMARK △ THIS PRODUCT SHALL BE MATED WITH DH40-37S OR DH3 * B-37S, IT APPLIES TO DH40-37S OR DH3 * B-37S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS. △ Unless otherwise specified, refer to IEC 60512.			APPROVED	KN. ICHIKAWA	20100705
			CHECKED	KN. ICHIKAWA	20100705
			DESIGNED	TU. TANIGUCHI	20100705
			DRAWN	TU. TANIGUCHI	20100705
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC-126592-00-00
HRS	SPECIFICATION SHEET		PART NO.	DH-37-CV2B	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL244-0015-9-00	△ 1/1