

APPLICABLE STANDARD						
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C		
	OPERATING&STORAGE HUMIDTY RANGE	85 % MAX	APPLICABLE CABLE	CABLE DIAMETER : $\phi 9.6\pm0.5$		
SPECIFICATIONS						
ITEM		TEST METHOD		REQUIREMENTS		QT AT
CONSTRUCTION						
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		X X
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED		CHECKED	DATE
						
REMARK Unless otherwise specified, refer to JIS C 5402.			APPROVED	A0. SUZUKI	09. 10. 05	
			CHECKED	KN. ICHIKAWA	09. 10. 02	
			DESIGNED	TU. TANIGUCHI	09. 10. 02	
			DRAWN	TU. TANIGUCHI	09. 10. 02	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-126660-00	
	SPECIFICATION SHEET		PART NO.	DH-51-CMB (9. 6)		
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL244-0034-3-00		1/