

Jun.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25 °C TO +85 °C	STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C	
	VOLTAGE	AC 100 V , DC 140 V	APPLICABLE CABLE	—————	
	CURRENT	5 A			
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X	
MARKING	CONFIRMED VISUALLY.		X	X	
ELECTRIC CHARACTERISTICS					
CONTACT RESISTANCE	CONTACT SHALL BE MEASURED AT DC 1 A	10 mΩ MAX.	X	—	
INSULATION RESISTANCE	500 V DC.	1000 MΩ MIN.	X	—	
VOLTAGE PROOF	1000 V AC. FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	—	
MECHANICAL CHARACTERISTICS					
CONTACT RETENTION FORCES	APPLYING A PULL THE WIRE AFTER THE APPLICABLE CRIMPED CONTACT IS ASSEMBLE THE BODY.	50 N MIN.	X	—	
CONNECTOR INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.	INSERTION AND WITHDRAWAL FORCES LOCKING DEVICE WITH UNLOCK : 34 N MAX	X	—	
MECHANICAL OPERATION	500 TIMES INSERTIONS AND EXTRACTIONS.	CONTACT RESISTANCE: 10 mΩ MAX.	X	—	
VIBRATION	FREQUENCY: 10 → 55 (Hz), SINGLE AMPLITUDE 0.75 mm, AT 2 h , FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 10 μs. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.	X	—	
SHOCK	AT 490 m/s ² DURATIONS OF PULSE 11 ms AT 3 TIMES FOR 6 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 10 μs. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.	X	—	
ENVIRONMENTAL CHARACTERISTICS					
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 °C, 90 TO 95 %, 96 h.	① INSULATION RESISTANCE: 10 MΩ MIN (AT HIGH HUMIDITY). ② INSULATION RESISTANCE: 100 MΩ MIN (AT DRY). ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—	
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -40→ R/T ⁽¹⁾ → +100 → R/T °C TIME 30 →10 TO 15→ 30 →10 TO 15 min UNDER 5 CYCLES.	① INSULATION RESISTANCE: 1000 MΩ MIN. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—	
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 500 h.	NO HEAVY CORROSION RUIN THE FUNCTION.	X	—	
DRY HEAT	EXPOSED AT +100 °C , 96 h.	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—	
COLD	EXPOSED AT -40 °C , 96 h.	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—	
SEALING ⁽²⁾	EXPOSED AT A DEPTH OF 1.8 m FOR 48 h.	NO WATER PENETRATION INSIDE CONNECTOR.	X	—	
AIRTIGHTNESS ⁽²⁾	APPLY AIR PRESSURE 18 kPa FOR 30 S TO INSIDE CONNECTOR.	NO AIR BUBBLES INSIDE CONNECTOR.	X	—	
△	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
REMARK			APPROVED	HY. KOBAYASHI	18.02.26
NOTES (1) R/T : ROOM TEMPERATURE.			CHECKED	HY. KOBAYASHI	18.02.26
(2) SEALING AND AIRTIGHTNESS SHALL BE TESTED UNDER MATED CONDITION WITH AN APPLICABLE CONNECTOR.			DESIGNED	TH. KAMEYA	18.02.24
(3) ABOVE SPECIFICATIONS ARE FOR THE STATE THAT APPLICABLE CRIMP CONTACTS ARE ASSEMBLED.			DRAWN	MK. INOUE	18.02.14
Unless otherwise specified, refer to IEC 60512 (JIS C 5402).					
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.	ELC-110655-31-00	
HRS	SPECIFICATION SHEET		PART NO.	JR16WP-10SC (31)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL114-2122-0-31	△ 1/1