

SEARCH OUR
PRODUCTS

aluminum
electrolytic &
organic
semiconductor

film

power film

tantalum
ceramic

TECH TOOLS



NEW PRODUCTS

Aluminum Electrolytic Capacitors

+105°C Standard Radial Lead Aluminum Electrolytic Capacitors

Part Number: 338CKE035M

[General Specifications \(PDF\)](#)

[Special Order Options](#)

[CKH_CKE document \(PDF\)](#)



Electrical Specifications

Capacitance: 3,300.0 μ F
Tolerance: -20 %, +20 %
Dissipation Factor: 0.18 at 120 Hz
ESR: 0.091 Ohms at 20° C and 120 Hz
Impedance:
 --
 --

Temperature Range: -55°C to +105°C

WVDC: 35 volts DC

SVDC: 44. volts DC

Leakage Current:
 1,155.0 μ A after 1 Minute

Ripple Current:
 1,560.0 mA at 120 Hz and 105°C

Impedance Ratios:

2.0 at -25°C/20°C

3.0 at -40°C/20°C

Load Life:

2000 Hours at 105°C with 100% of rated voltage and
 with 0% of rated ripple current

Physical Specifications

Diameter (D): 16.0 mm + 0.5 mm
Length (L): 35.5 mm + 1.5 mm
Lead Wire Diameter (d): 0.8 mm + 0.05 mm
Lead Spacing: 7.5 mm +/- 0.5 mm
Lead Length: 15 mm

