

[Home](#) > [Products](#) > [Other](#) > [Miscellaneous](#) > [9UM702](#) > 9UM702BKLF

**9UM702BKLF**

|               |               |
|---------------|---------------|
| Category:     | Miscellaneous |
| Generic Part: | 9UM702        |
| Description:  | PC MAIN CLOCK |

You may also like...

## Time is money

## Parameters

|             |           |
|-------------|-----------|
| Package     | VFQFPN 48 |
| Speed       | NA        |
| Temperature | C         |
| Voltage     | 3.3 V     |

## Sales and Support

## Sales Offices

► Sales Offices and authorized distributors

## Technical Support

Clock Help

► WWW: Clock Help

[illegible]

## Package

|                                  |                                      |
|----------------------------------|--------------------------------------|
| Package                          | VFQFPN 48 (NDG48)                    |
| Description                      | VFQFP-N 6.0 X 6.0 X 0.9 MM - NO LEAD |
| Status                           | Active                               |
| Class                            | PLASTIC                              |
| Category                         | Green                                |
| Pb (Lead) Free                   | Yes                                  |
| Pb Free Category                 | e3 Sn                                |
| Mark                             | K                                    |
| Package Type                     | VFQFPN                               |
| Lead Count                       | 48                                   |
| Length                           | 6.0 mm                               |
| Width                            | 6.0 mm                               |
| Thickness                        | 0.9 mm                               |
| Pitch                            | 0.4 mm                               |
| Tube / Tray                      | TRAY                                 |
| Quantity per Tube/Tray           | 490                                  |
| Quantity per Reel                | 1000                                 |
| Moisture Sensitivity Level (MSL) | 1                                    |
| Moisture Exposure Floor Life     | Unlimited@<30C/85%RH                 |
| Peak Reflow Temperature          | 260°C                                |
| Rebake Conditions                | NA                                   |
| Related Package Documents        | <a href="#">view documents</a>       |

## Distributor Inventory

No Pricing information is available from our Distributors at this time.

## Documents

No documents available for this part at this time.