



# Intel® Core™ i3-530 Processor (4M Cache, 2.93 GHz)

Add to Compare

## SPECIFICATIONS

### Essentials

- Memory Specifications
- Graphics Specifications
- Expansion Options
- Package Specifications
- Advanced Technologies
- Intel® Data Protection Technology
- Intel® Platform Protection Technology

## COMPATIBLE PRODUCTS

## PRODUCT IMAGES

## ORDERING / SSPECS / STEPPINGS

## SPECIFICATIONS

### Essentials

Status	End of Life
Launch Date	Q1'10
Processor Number	i3-530
# of Cores	2
# of Threads	4
Clock Speed	2.93 GHz
Intel® Smart Cache	4 MB
DMI	2.5 GT/s
Instruction Set	64-bit
Instruction Set Extensions	SSE4.2
Embedded Options Available	No
Lithography	32 nm
Max TDP	73 W
VID Voltage Range	0.6500V-1.400V
Recommended Customer Price	

### Memory Specifications

Max Memory Size (dependent on memory type)	16 GB
Memory Types	DDR3-1066/1333
# of Memory Channels	2
Max Memory Bandwidth	21 GB/s
Physical Address Extensions	36-bit

### Graphics Specifications

Processor Graphics ‡	Intel® HD Graphics
----------------------	--------------------

## RELATED PRODUCTS

- Previous Generation Intel® Core™ i3 Processor
- Intel® Core™ i3-500 Desktop Processor Series
- Products formerly Clarkdale

## QUICK LINKS

- Download Datasheet
- Export Full Specifications
- Find Compatible Boards
- Search Distributors
- Support Overview
- Search all of intel.com

## PCN/MDDS INFORMATION








**SLBLR**  
904341: [PCN](#) | [MDDS](#)  
904852: [PCN](#) | [MDDS](#)  
**SLBX7**  
907938: [PCN](#) | [MDDS](#)

Intel® Flexible Display Interface (Intel® FDI)	yes
Intel® Clear Video HD Technology	Yes
# of Displays Supported ‡	2


### Expansion Options

PCI Express Revision	2.0
PCI Express Configurations ‡	1x16, 2x8
Max # of PCI Express Lanes	16

Package Specifications	
Max CPU Configuration	1
T <sub>J</sub> CASE	72.6°C
Package Size	37.5mm x 37.5mm
Processing Die Size	81 mm²
# of Processing Die Transistors	382 million
Graphics and IMC Lithography	45 nm
Graphics and IMC Die Size	114 mm²
# of Graphics and IMC Die Transistors	177 million
Sockets Supported	FCLGA1156
Low Halogen Options Available	See MDDS

Advanced Technologies	
Intel® Turbo Boost Technology ‡	No
Intel® vPro Technology ‡	 No
Intel® Hyper-Threading Technology ‡	 Yes
Intel® Virtualization Technology (VT-x) ‡	 Yes
Intel® VT-x with Extended Page Tables (EPT) ‡	 Yes
Intel® 64 ‡	 Yes
Idle States	Yes
Enhanced Intel SpeedStep® Technology	 Yes
Intel® Demand Based Switching	 No
Thermal Monitoring Technologies	No

Intel® Data Protection Technology	
AES New Instructions	 No

Intel® Platform Protection Technology	
Trusted Execution Technology ‡	 No
Execute Disable Bit ‡	Yes

All information provided is subject to change at any time, without notice. Intel may make changes to manufacturing life cycle, specifications, and product descriptions at any time, without notice. The information herein is provided "as-is" and Intel does not make any representations or warranties whatsoever regarding accuracy of the information, nor on the product features, availability, functionality, or compatibility of the products listed. Please contact system vendor for more information on specific products or systems.

"Intel classifications" consist of Export Control Classification Numbers (ECCN) and Harmonized Tariff Schedule (HTS) numbers. Any use made of Intel classifications are without recourse to Intel and shall not be construed as a representation or warranty regarding the proper ECCN or HTS. Your company may be the exporter of record, and as such, your company is responsible for determining the correct classification of any item at the time of export.

"Announced" SKUs are not yet available. Please refer to the Launch Date for market availability.

Some products can support AES New Instructions with a Processor Configuration update, in particular, i7-2630QM/i7-2635QM, i7-2670QM/i7-2675QM, i5-2430M/i5-2435M, i5-2410M/i5-2415M. Please contact OEM for the BIOS that includes the latest Processor configuration update.

‡ This feature may not be available on all computing systems. Please check with the system vendor to determine if your system delivers this feature, or reference the system specifications (motherboard, processor, chipset, power supply, HDD, graphics controller, memory, BIOS, drivers, virtual machine monitor-VMM, platform software, and/or operating system) for feature compatibility. Functionality, performance, and other benefits of this feature may vary depending on system configuration.

See <http://www.intel.com/content/www/us/en/architecture-and-technology/hyper-threading/hyper-threading-technology.html?wapkw=hyper+threading> for more information including details on which processors support Intel® HT Technology.

Max Turbo Frequency refers to the maximum single-core processor frequency that can be achieved with Intel® Turbo Boost Technology. See [www.intel.com/technology/turboboost/](http://www.intel.com/technology/turboboost/) for more information.

The Recommended Customer Price ("RCP") is pricing guidance for Intel products. Prices are for direct Intel customers and are subject to change without notice. Taxes and shipping, etc. not included. Prices may vary for other package types and shipment quantities, and special promotional arrangements may apply. Listing of these RCP does not constitute a formal pricing offer from Intel. Please work with your appropriate Intel representative to obtain a formal price quotation.


System and Maximum TDP is based on worst case scenarios. Actual TDP may be lower if not all I/Os for chipsets are used.

Low Halogen: Applies only to brominated and chlorinated flame retardants (BFRs/CFRs) and PVC in the final product. Intel components as well as purchased components on the finished assembly meet JS-709 requirements, and the PCB / substrate meet IEC 61249-2-21 requirements. The replacement of halogenated flame retardants and/or PVC may not be better for the environment.

For benchmarking data see <http://www.intel.com/performance>.

Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different processor families. See <http://www.intel.com/content/www/us/en/processors/processor-numbers.html> for details.

Processors that support 64-bit computing on Intel® architecture require an Intel 64 architecture-enabled BIOS.

 [Send us your feedback!](#)

