




Intel® Xeon® Processor E5-2430 v2 (15M Cache, 2.50 GHz)

Specifications

- Essentials

| | |
|----------------------------|---|
| Status | Launched |
| Launch Date | Q1'14 |
| Processor Number | E5-2430V2 |
| Intel® Smart Cache | 15 MB |
| Intel® QPI Speed | 7.2 GT/s |
| # of QPI Links | 1 |
| Instruction Set | 64-bit |
| Instruction Set Extensions | AVX |
| Embedded Options Available |  Yes |
| Lithography | 22 nm |
| Scalability | 2S Only |
| VID Voltage Range | 0.65-1.30V |
| Recommended Customer Price | TRAY: \$551.00 |
| Conflict Free | Yes |
| Datasheet | Link |
| Additional Information URL | Link |

- Performance









| | |
|--------------------------|---------|
| # of Cores | 6 |
| # of Threads | 12 |
| Processor Base Frequency | 2.5 GHz |
| Max Turbo Frequency | 3 GHz |
| TDP | 80 W |

- Memory Specifications

| | |
|--|---|
| Max Memory Size (dependent on memory type) | 384 GB |
| Memory Types | DDR3 800/1066/1333/1600 |
| Max # of Memory Channels | 3 |
| Max Memory Bandwidth | 38.4 GB/s |
| Physical Address Extensions | 46-bit |
| ECC Memory Supported † |  Yes |

- Expansion Options

| | |
|--|--|
| | |
|--|--|

| | | |
|--|---|---------------|
| PCI Express Revision | | 3.0 |
| PCI Express Configurations † | | x4, x8, x16 |
| Max # of PCI Express Lanes | | 24 |
| - Package Specifications | | |
| Max CPU Configuration | | 2 |
| T _{CASE} | | 76°C |
| Package Size | | 45mm x 42.5mm |
| Sockets Supported | | FCLGA1356 |
| Low Halogen Options Available | | See MDDS |
| - Advanced Technologies | | |
| Intel® Turbo Boost Technology † | | 2.0 |
| Intel® Hyper-Threading Technology † |  | Yes |
| Intel® Virtualization Technology (VT-x) † | | Yes |
| Intel® Virtualization Technology for Directed I/O (VT-d) † |  | Yes |
| Intel® VT-x with Extended Page Tables (EPT) † |  | Yes |
| Intel® TSX-NI | | No |
| Intel® 64 † |  | Yes |
| Idle States | | Yes |
| Enhanced Intel SpeedStep® Technology |  | Yes |
| Intel® Demand Based Switching |  | Yes |
| Thermal Monitoring Technologies | | Yes |
| Intel® Flex Memory Access | | No |
| Intel® Identity Protection Technology † | | No |
| - Intel® Data Protection Technology | | |
| Intel® AES New Instructions |  | Yes |
| Secure Key | | Yes |
| - Intel® Platform Protection Technology | | |
| OS Guard | | Yes |
| Trusted Execution Technology † |  | Yes |
| Execute Disable Bit † | | Yes |

Compatible Products

| | | | | | |
|----------------|---------------------|---------------|----------------------------|--------------------------|---------------|
| - System | | | | | |
| Compare | Product Name | Status | Chassis Form Factor | Board Form Factor | Socket |
| Compare All + | | | | | |

| | | | | | |
|--|--|-------------|-------------|-----------------------|-----------|
| | Intel® Server System R1208BB4DC | End of Life | 1U Rack | Custom 13.5" x 13.5" | Socket B2 |
| | Intel® Server System R1208BB4GS9 | End of Life | 1U Rack | Custom 13.5" x 13.5" | Socket B2 |
| | Intel® Server System R1304BB4DC | End of Life | 1U Rack | Custom 13.5" x 13.5" | Socket B2 |
| | Intel® Server System R1304BB4GS9 | End of Life | 1U Rack | Custom 13.5" x 13.5" | Socket B2 |
| | Intel® Server System R1304SP2SFBN | End of Life | 1U Rack | SSI ATX (12" X 9.6") | Socket B2 |
| | Intel® Server System R1304SP2SHBN | End of Life | 1U Rack | ATX | Socket R3 |
| | Intel® Server System R1304SP4SHOC | Launched | 1U Rack | ATX 12" x 9.6" | Socket B2 |
| | Intel® Server System R2000BB4GS9 | End of Life | 2U Rack | Custom 13.5" x 13.5" | Socket B2 |
| | Intel® Server System R2208BB4GC | End of Life | 2U Rack | Custom 13.5" x 13.5" | Socket B2 |
| | Intel® Server System R2208BB4GS9 | End of Life | 2U Rack | Custom 13.5" x 13.5" | Socket B2 |
| | Intel® Server System R2216BB4GC | End of Life | 2U Rack | Custom 13.5" x 13.5" | Socket B2 |
| | Intel® Server System R2224BB4GCSAS | End of Life | 2U Rack | Custom 13.5" x 13.5" | Socket B2 |
| | Intel® Server System R2308BB4GC | End of Life | 2U Rack | Custom 13.5" x 13.5" | Socket B2 |
| | Intel® Server System R2312BB4GS9 | End of Life | 2U Rack | Custom 13.5" x 13.5" | Socket B2 |
| | Intel® Server System R2308SC2SHDR | End of Life | 2U Rack | SSI CEB (12" X 10.5") | Socket B2 |
| | Intel® Server System R2308SC2SHFN | End of Life | 2U Rack | SSI CEB 12" X 10.5" | Socket B2 |
| | Intel® Server System R2312SC2SHGR | End of Life | 2U Rack | SSI CEB 12" X 10.5" | Socket B2 |
| | Intel® Server System P4304SC2SFEN | End of Life | 4U Pedestal | SSI CEB 12" X 10.5" | Socket B2 |
| | Intel® Server System P4304SC2SHDR | End of Life | 4U Pedestal | SSI CEB (12" X 10.5") | Socket B2 |
| | Intel® Server System P4308SC2MHGC | End of Life | 4U Pedestal | SSI CEB 12" X 10.5" | Socket B2 |

- Server/Workstation Board

| Compare | Product Name | Status | Board Form Factor | Chassis Form Factor | Socket | Embedded Options Available | TDP |
|---------------|--|-------------|----------------------|---------------------|-----------|----------------------------|------|
| Compare All + | Intel® Server Board S1400FP2 | Launched | ATX | 4U Rack or Pedestal | Socket B2 | No | 95 W |
| | Intel® Server Board S1400FP4 | Launched | ATX | 4U Rack or Pedestal | Socket B2 | No | 95 W |
| | Intel® Server Board S1400SP2 | End of Life | ATX | 1U Rack | Socket B2 | Yes | 95 W |
| | Intel® Server Board S1400SP4 | Launched | SSI ATX 12" X 9.6" | 1U Rack | Socket B2 | Yes | 95 W |
| | Intel® Server Board S2400BB4 | End of Life | Custom 13.5" x 13.5" | Rack | Socket B2 | No | 95 W |
| | Intel® Server Board S2400EP2 | End of Life | SSI CEB 12" x 10.5" | 1U Rack | Socket B2 | Yes | 95 W |
| | Intel® Server Board S2400EP4 | End of Life | SSI CEB 12" x 10.5" | 1U Rack | Socket B2 | Yes | 95 W |
| | Intel® Server Board S2400LP | End of Life | Custom 6.8" x 16.6" | 2U Rack | Socket B2 | No | 95 W |
| | Intel® Server Board S2400SC2 | End of Life | SSI CEB 12" x 10.5" | 4U Rack or Pedestal | Socket B2 | No | 95 W |

Ordering and Spec Information

Trade Compliance Information

| ECCN | CCATS | US HTS |
|--------|---------|------------------|
| 5A992C | G077159 | 8542310000-HYBRD |

Ordering and Spec Information

| Spec Code | Ordering Code | Step | RCP |
|---|-----------------|------|----------|
| Intel® Xeon® Processor E5-2430 v2 (15M Cache, 2.50 GHz) FC-LGA12A, Tray | | | |
| SR1AH | CM8063401286400 | S1 | \$551.00 |

Download Drivers

**BIOS Implementation Test Suite (BITS)**

This download installs version build 2073 of the BIOS Implementation Test Suite (BITS).

Version: Build 2073 (Latest)

Date: 2/2/2016

Operating Systems: OS Independent

**Intel® Processor Diagnostic Tool**

This download installs the Intel® Processor Diagnostic Tool release 3.0.0.25, which is compatible with multiprocessor systems.

Version: 3.0.0.25 (Latest)

Date: 1/25/2016

Operating Systems: Linux*, Windows 7*, Windows Server 2008 R2*, 5 more

**Linux* Processor Microcode Data File**

The microcode data file contains the latest microcode definitions for all Intel® Processors. Intel periodically releases these microcode updates.

Version: 20150121 (Previously Released)

Date: 1/21/2015

Operating Systems: Turbolinux*, Red Hat Desktop 3 Update 4*, Red Hat Desktop Linux 3*, 90 more

**Linux* Processor Microcode Data File**

The microcode data file 20150107 for Linux* contains the latest microcode definitions for all Intel® Processors. Intel periodically releases these microcode updates.

Version: 20150107 (Previously Released)

Date: 1/7/2015

Operating Systems: Turbolinux*, Red Hat Desktop 3 Update 4*, Red Hat Desktop Linux 3*, 88 more

**Linux* Processor Microcode Data File**

The microcode data file 20140913 for Linux* contains the latest microcode definitions for all Intel® Processors. Intel periodically releases these microcode updates.

Version: 20140913 (Previously Released)

Date: 9/15/2014

Operating Systems: Red Hat Desktop 3 Update 4*, Red Hat Desktop Linux 3*, Red Hat Enterprise Linux 2.1*, 81 more

**Linux* Processor Microcode Data File**

The microcode data file 20140624 for Linux* contains the latest microcode definitions for all Intel® Processors. Intel periodically releases these microcode updates.

Version: 20140624 (Previously Released)

Date: 6/24/2014

Operating Systems: Linux*

**Linux* Processor Microcode Data File**

The microcode data file 20140430 for Linux* contains the latest microcode definitions for all Intel® Processors. Intel periodically releases these microcode updates.

Version: 20140430 (Previously Released)

Date: 4/30/2014

Operating Systems: Linux*

**Linux* Processor Microcode Data File**

The microcode data file 20140122 for Linux* contains the latest microcode definitions for all Intel® Processors. Intel periodically releases these microcode updates.

Version: 20140122 (Previously Released)

Date: 1/22/2014

Operating Systems: Turbolinux*, Red Hat Desktop 3 Update 4*, Red Hat Desktop Linux 3*, 79 more

**Linux* Processor Microcode Data File**

The microcode data file 20130906 for Linux* contains the latest microcode definitions for all Intel® Processors. Intel periodically releases these microcode updates.

Version: 20130906 (Previously Released)

Date: 9/6/2013

Operating Systems: Turbolinux*, Red Hat Desktop 3 Update 4*, Red Hat Desktop Linux 3*, 79 more

**Linux* Processor Microcode Data File**

The microcode data file 20130808 for Linux* contains the latest microcode definitions for all Intel® Processors. Intel periodically releases these microcode updates.

Version: 20130808 (Previously Released)

Date: 8/14/2013

Operating Systems: Turbolinux*, Red Hat Desktop 3 Update 4*, Red Hat Desktop Linux 3*, 79 more

**Linux* Processor Microcode Data File**

The microcode data file 20130222 for Linux* contains the latest microcode definitions for all Intel® Processors. Intel periodically releases these microcode updates.

Version: 20130222 (Previously Released)

Date: 2/25/2013

Operating Systems: Turbolinux*, Red Hat Desktop 3 Update 4*, Red Hat Desktop Linux 3*, 74 more

**Linux* Processor Microcode Data File**

The microcode data file 20120606-v2 for Linux* contains the latest microcode definitions for all Intel® Processors. Intel periodically releases these microcode updates.

Version: 20120606-v2 (Previously Released)

Date: 10/1/2012

Operating Systems: Turbolinux*, Red Hat Desktop 3 Update 4*, Red Hat Desktop Linux 3*, 72 more

**Linux* Processor Microcode Data File**

The microcode data file 20120606 for Linux* contains the latest microcode definitions for all Intel® Processors. Intel periodically releases these microcode updates.

Version: 20120606 (Previously Released)

Date: 6/6/2012

Operating Systems: Turbolinux*, Red Hat Desktop 3 Update 4*, Red Hat Desktop Linux 3*, 72 more

**Display Drivers for Intel® Core™ Processors on 64-bit Windows 7* and Windows Embedded Standard 7***

This download installs version 15.22.54.64.2622 of the display drivers for Intel® Core™ Processors for Windows* 7, 64-bit and Windows Embedded Standard 7.

Version: 15.22.54.64.2622 (Previously Released)

Date: 1/1/2012

Operating Systems: Windows 7, 64-bit*, Windows Embedded Standard 7*

**Linux* Processor Microcode Data File**

The microcode data file 20111110 for Linux* contains the latest microcode definitions for all Intel® Processors. Intel periodically releases these microcode updates.

Version: 20111110 (Previously Released)

Date: 12/12/2011

Operating Systems: Turbolinux*, Red Hat Desktop 3 Update 4*, Red Hat Desktop Linux 3*, 70 more

**Linux* Processor Microcode Data File**

The microcode data file 20110915 for Linux* contains the latest microcode definitions for all Intel® Processors.

Version: 20110915 (Previously Released)

Date: 9/13/2011

Operating Systems: Turbolinux*, Red Hat Desktop 3 Update 4*, Red Hat Desktop Linux 3*, 70 more

**Linux* Processor Microcode Data File**

The microcode data file 20110428 for Linux* contains the latest microcode definitions for all Intel® Processors.

Version: 20110428 (Previously Released)

Date: 4/24/2011

Operating Systems: Turbolinux*, Red Hat Desktop 3 Update 4*, Red Hat Desktop Linux 3*, 70 more

**Linux* Processor Microcode Data File**

The microcode data file 20101123 for Linux* contains the latest microcode definitions for all Intel® Processors.

Version: 20101123 (Previously Released)

Date: 11/20/2010

Operating Systems: Turbolinux*, Red Hat Desktop 3 Update 4*, Red Hat Desktop Linux 3*, 70 more

**Linux* Processor Microcode Data File**

The microcode data file 20100914 for Linux* contains the latest microcode definitions for all Intel® Processors.

Version: 20100914 (Previously Released)

Date: 9/11/2010

Operating Systems: Turbolinux*, Red Hat Desktop 3 Update 4*, Red Hat Desktop Linux 3*, 70 more

**Linux* Processor Microcode Data File**

The microcode data file 201000826 for Linux* contains the latest microcode definitions for all Intel® Processors.

Version: 201000826 (Previously Released)

Date: 8/21/2010

Operating Systems: Turbolinux*, Red Hat Desktop 3 Update 4*, Red Hat Desktop Linux 3*, 70 more

All information provided is subject to change at any time, without notice. Intel may make changes to manufacturing life cycle, specifications, and product descriptions at any time, without notice. The information herein is provided "as-is" and Intel does not make any representations or warranties whatsoever regarding accuracy of the information, nor on the product features, availability, functionality, or compatibility of the products listed. Please contact system vendor for more information on specific products or systems.

"Intel classifications" consist of Export Control Classification Numbers (ECCN) and Harmonized Tariff Schedule (HTS) numbers. Any use made of Intel classifications are without recourse to Intel and shall not be construed as a representation or warranty regarding the proper ECCN or HTS. Your company may be the exporter of record, and as such, your company is responsible for determining the correct classification of any item at the time of export.

Refer to Datasheet for formal definitions of product properties and features.

"Announced" SKUs are not yet available. Please refer to the Launch Date for market availability.

Some products can support AES New Instructions with a Processor Configuration update, in particular, i7-2630QM/i7-2635QM, i7-2670QM/i7-2675QM, i5-2430M/i5-2435M, i5-2410M/i5-2415M. Please contact OEM for the BIOS that includes the latest Processor configuration update.

‡ This feature may not be available on all computing systems. Please check with the system vendor to determine if your system delivers this feature, or reference the system specifications (motherboard, processor, chipset, power supply, HDD, graphics controller, memory, BIOS, drivers, virtual machine monitor-VMM, platform software, and/or operating system) for feature compatibility. Functionality, performance, and other benefits of this feature may vary depending on system configuration.

"Conflict free" and "conflict-free" means "DRC conflict free", which is defined by the U.S. Securities and Exchange Commission rules to mean products that do not contain conflict minerals (tin, tantalum, tungsten and/or gold) that directly or indirectly finance or benefit armed groups in the Democratic Republic of the Congo (DRC) or adjoining countries. Intel also uses the term "conflict-free" in a broader sense to refer to suppliers, supply chains, smelters and refiners whose sources of conflict minerals do not finance conflict in the DRC or adjoining countries. Intel processors manufactured before January 1, 2013 are not confirmed conflict free. The conflict free designation refers only to product manufactured after that date. For Intel Boxed Processors, the conflict free designation refers to the processor only, not to any additional included accessories, such as heatsinks/coolers.

See <http://www.intel.com/content/www/us/en/architecture-and-technology/hyper-threading/hyper-threading-technology.html?wapkw=hyper+threading> for more information including details on which processors support Intel® HT Technology.

Max Turbo Frequency refers to the maximum single-core processor frequency that can be achieved with Intel® Turbo Boost Technology. See www.intel.com/technology/turboboost/ for more information.

The Recommended Customer Price ("RCP") is pricing guidance for Intel products. Prices are for direct Intel customers, typically represent 1,000-unit purchase quantities, and are subject to change without notice. Taxes and shipping, etc. not included. Prices may vary for other package types and shipment quantities, and special promotional arrangements may apply. If sold in bulk, price represents individual unit. Listing of these RCP does not constitute a formal pricing offer from Intel. Please work with your appropriate Intel representative to obtain a formal price quotation.

System and Maximum TDP is based on worst case scenarios. Actual TDP may be lower if not all I/Os for chipsets are used.

Low Halogen: Applies only to brominated and chlorinated flame retardants (BFRs/CFRs) and PVC in the final product. Intel components as well as purchased components on the finished assembly meet JS-709 requirements, and the PCB / substrate meet IEC 61249-2-21 requirements. The replacement of halogenated flame retardants and/or PVC may not be better for the environment.

For benchmarking data see <http://www.intel.com/performance>.

Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different processor families. See <http://www.intel.com/content/www/us/en/processors/processor-numbers.html> for details.

Processors that support 64-bit computing on Intel® architecture require an Intel 64 architecture-enabled BIOS.

[Send us your feedback!](#)