

Support Home > Product Specifications > Processors







Intel[®] Core[™] i5-7400T Processor

"rocessor Graphics ‡ ?

6M Cache, up to 3.00 GHz

Add to Compare

Intel® HD Graphics 630

Specifications

Essentials

Performance

Supplemental Information

Memory Specifications

Processor Graphics

Expansion Options

Package Specifications

Advanced Technologies

Security & Reliability

Ordering and Compliance

Compatible Products

Downloads and Software

Essentials	Export specification	
Product Collection	7th Generation Intel® Core™ i5 Processors	
Code Name	Products formerly Kaby Lake	
Vertical Segment	Desktop	
Processor Number	i5-7400T	
Status	Launched	
Launch Date ?	Q1'17	
Lithography ?	14 nm	
Recommended Customer Price ?	-	
Performance		
# of Cores ?	4	
# of Threads ?	4	
Processor Base Frequency ?	2.40 GHz	
Max Turbo Frequency 😯	3.00 GHz	
Cache ?	6 MB SmartCache	
Bus Speed ?	8 GT/s DMI3	
# of QPI Links ?	0	
TDP ?	35 W	
Configurable TDP-down Frequency ?	1.20 GHz	
Supplemental Information		
Embedded Options Available 🔞	No	
Datasheet	View now	
Memory Specifications		
Max Memory Size (dependent on memory type)	? 64 GB	
Memory Types ?	DDR4-2133/2400, DDR3L-1333/1600 @ 1.35V	
Max # of Memory Channels ?	2	
ECC Memory Supported ‡ ?	No	
Processor Graphics		

Graphics Base Frequency ?	350 MH
Graphics Max Dynamic Frequency 🔞	1.00 GF
Graphics Video Max Memory 🕐	64 0
4K Support 🔞	Yes, at 60H
Max Resolution (HDMI 1.4)‡ 🕡	4096x2304@24F
Max Resolution (DP)‡ 🕐	4096x2304@60H
Max Resolution (eDP - Integrated Flat Panel)‡ 👔	4096x2304@60H
DirectX* Support ?	1
OpenGL* Support 😨	4
Intel® Quick Sync Video 💿	Y
Intel® InTru™ 3D Technology 🕐	Ye
Intel® Clear Video HD Technology 🔞	Y
Intel® Clear Video Technology 💽	Ye
# of Displays Supported [‡]	
Device ID	0x59 ⁻
Expansion Options	
Scalability	1S On
PCI Express Revision ?	3
PCI Express Configurations ‡ ?	Up to 1x16, 2x8, 1x8+2x
PCI Express Configurations ‡ ? Max # of PCI Express Lanes ? Package Specifications	
PCI Express Configurations ‡ ? Max # of PCI Express Lanes ? Package Specifications Sockets Supported ?	
PCI Express Configurations ‡ ? Max # of PCI Express Lanes ? Package Specifications Sockets Supported ? Max CPU Configuration	FCLGA11
PCI Express Configurations † ? Max # of PCI Express Lanes ? Package Specifications Sockets Supported ? Max CPU Configuration Thermal Solution Specification ?	FCLGA11
PCI Express Configurations † ? Max # of PCI Express Lanes ? Package Specifications Sockets Supported ? Max CPU Configuration Thermal Solution Specification ? TJUNCTION ?	FCLGA115 PCG 2015A (35)
PCI Express Configurations † ? Max # of PCI Express Lanes ? Package Specifications Sockets Supported ? Max CPU Configuration Thermal Solution Specification ?	FCLGA115 PCG 2015A (35)
PCI Express Configurations † ? Max # of PCI Express Lanes ? Package Specifications Sockets Supported ? Max CPU Configuration Thermal Solution Specification ? TJUNCTION ?	FCLGA115 PCG 2015A (35V 80° 37.5mm x 37.5m
PCI Express Configurations † ? Max # of PCI Express Lanes ? Package Specifications Sockets Supported ? Max CPU Configuration Thermal Solution Specification ? TJUNCTION ? Package Size	FCLGA115 PCG 2015A (35V 80° 37.5mm x 37.5m
PCI Express Configurations † ? Max # of PCI Express Lanes ? Package Specifications Sockets Supported ? Max CPU Configuration Thermal Solution Specification ? TJUNCTION ? Package Size Low Halogen Options Available	FCLGA115 PCG 2015A (35V 80° 37.5mm x 37.5m See MDE
PCI Express Configurations † ?? Max # of PCI Express Lanes ? Package Specifications Sockets Supported ? Max CPU Configuration Thermal Solution Specification ? TJUNCTION ? Package Size Low Halogen Options Available Advanced Technologies	FCLGA115 PCG 2015A (35V 80° 37.5mm x 37.5m See MDD
PCI Express Configurations ‡ ?? Max # of PCI Express Lanes ? Package Specifications Sockets Supported ? Max CPU Configuration Thermal Solution Specification ? TJUNCTION ? Package Size Low Halogen Options Available Advanced Technologies Intel® Optane™ Memory Supported ‡ ?	FCLGA115 PCG 2015A (35V 80° 37.5mm x 37.5m See MDD
PCI Express Configurations ‡ ? Max # of PCI Express Lanes ? Package Specifications Sockets Supported ? Max CPU Configuration Thermal Solution Specification ? TJUNCTION ? Package Size Low Halogen Options Available Advanced Technologies Intel® Optane™ Memory Supported ‡ ? Intel® Turbo Boost Technology ‡ ?	FCLGA115 PCG 2015A (35V 80° 37.5mm x 37.5m See MDD
PCI Express Configurations ‡ ? Max # of PCI Express Lanes ? Package Specifications Sockets Supported ? Max CPU Configuration Thermal Solution Specification ? TJUNCTION ? Package Size Low Halogen Options Available Advanced Technologies Intel® Optane™ Memory Supported ‡ ? Intel® Turbo Boost Technology ‡ ? Intel® vPro™ Technology ‡ ?	FCLGA11! PCG 2015A (35\ 80' 37.5mm x 37.5m See MDE
PCI Express Configurations ‡ ? Max # of PCI Express Lanes ? Package Specifications Sockets Supported ? Max CPU Configuration Thermal Solution Specification ? TJUNCTION ? Package Size Low Halogen Options Available Advanced Technologies Intel® Optane™ Memory Supported ‡ ? Intel® Turbo Boost Technology ‡ ? Intel® vPro™ Technology ‡ ? Intel® Hyper-Threading Technology ‡ ?	FCLGA11! PCG 2015A (35\) 80' 37.5mm x 37.5m See MDE
PCI Express Configurations ‡ ? Max # of PCI Express Lanes ? Package Specifications Sockets Supported ? Max CPU Configuration Thermal Solution Specification ? TJUNCTION ? Package Size Low Halogen Options Available Advanced Technologies Intel® Optane™ Memory Supported ‡ ? Intel® Turbo Boost Technology ‡ ? Intel® tyPro™ Technology ‡ ? Intel® Hyper-Threading Technology † ? Intel® Virtualization Technology (VT-x) ‡ ?	FCLGA115 PCG 2015A (35V 80° 37.5mm x 37.5m See MDD
PCI Express Configurations ‡ ? Max # of PCI Express Lanes ? Package Specifications Sockets Supported ? Max CPU Configuration Thermal Solution Specification ? TJUNCTION ? Package Size Low Halogen Options Available Advanced Technologies Intel® Optane™ Memory Supported ‡ ? Intel® Turbo Boost Technology ‡ ? Intel® tyPro™ Technology † ? Intel® Hyper-Threading Technology † ? Intel® Virtualization Technology for Directed I/O (VT-d) ‡ ?	Up to 1x16, 2x8, 1x8+2x FCLGA115 PCG 2015A (35V 80° 37.5mm x 37.5mm See MDE Ye 2 N Ye Ye Ye Ye N

Idle States ?	Yes
Enhanced Intel SpeedStep® Technology ?	Yes
Thermal Monitoring Technologies ?	Yes
Intel® Identity Protection Technology ‡ ?	Yes
Intel® Stable Image Platform Program (SIPP)	No
Security & Reliability	
Intel® AES New Instructions ?	Yes
Secure Key ?	Yes
Intel® Software Guard Extensions (Intel® SGX)	Yes
Intel® Memory Protection Extensions (Intel® MPX) 🔞	Yes
Intel® OS Guard	Yes
Intel® Trusted Execution Technology ‡ 👔	No
Execute Disable Bit ‡ ?	Yes
	Yes

More support options for Intel® Core™ i5-7400T Processor (6M Cache, up to 3.00 GHz)





Downloads and Software



Support Community



Warranty and Replacement



Need more help?

Contact support



All information provided is subject to change at any time, without notice. Intel may make changes to manufacturing life cycle, specifications, and product descriptions at any time, without notice. The information herein is provided "as-is" and Intel does not make any representations or warranties whatsoever regarding accuracy of the information, nor on the product features, availability, functionality, or compatibility of the products listed. Please contact system vendor for more information on specific products or systems.

Intel classifications are for informational purposes only and consist of Export Control Classification Numbers (ECCN) and Harmonized Tariff Schedule (HTS) numbers. Any use made of Intel classifications are without recourse to Intel and shall not be construed as a representation or warranty regarding the proper ECCN or HTS. Your company as an importer and/or exporter is responsible for determining the correct classification of your transaction.

Refer to Datasheet for formal definitions of product properties and features.

"Announced" SKUs are not yet available. Please refer to the Launch Date for market availability.

Some products can support AES New Instructions with a Processor Configuration update, in particular, i7-2630QM/i7-2635QM, i7-2670QM/i7-2675QM, i5-2430M/i5-2435M, i5-2410M/i5-2415M. Please contact OEM for the BIOS that includes the latest Processor configuration update.

‡ This feature may not be available on all computing systems. Please check with the system vendor to determine if your system delivers this feature, or $reference \ the \ system \ specifications \ (mother board, processor, chipset, power \ supply, HDD, graphics \ controller, memory, BIOS, drivers, virtual \ machine$ monitor-VMM, platform software, and/or operating system) for feature compatibility. Functionality, performance, and other benefits of this feature may vary depending on system configuration.

"Conflict free" and "conflict-free" means "DRC conflict free", which is defined by the U.S. Securities and Exchange Commission rules to mean products that do not contain conflict minerals (tin, tantalum, tungsten and/or gold) that directly or indirectly finance or benefit armed groups in the Democratic Republic of the Congo (DRC) or adjoining countries. Intel also uses the term "conflict-free" in a broader sense to refer to suppliers, supply chains, ict minerals do not finance conflict in the DRC or adjoining countries. Intel processors manufactured before

Downloaded from Arrow.com.

January 1, 2013 are not confirmed conflict free. The conflict free designation refers only to product manufactured after that date. For Intel Boxed Processors, the conflict free designation refers to the processor only, not to any additional included accessories, such as heatsinks/coolers.

See http://www.intel.com/content/www/us/en/architecture-and-technology/hyper-threading/hyper-threading-technology.html? wapkw=hyper+threading for more information including details on which processors support Intel® HT Technology.

Max Turbo Frequency refers to the maximum single-core processor frequency that can be achieved with Intel® Turbo Boost Technology. See www.intel.com/technology/turboboost/ for more information.

The Recommended Customer Price ("RCP") is pricing guidance for Intel products. Prices are for direct Intel customers, typically represent 1,000-unit purchase quantities, and are subject to change without notice. Taxes and shipping, etc. not included. Prices may vary for other package types and shipment quantities, and special promotional arrangements may apply. If sold in bulk, price represents individual unit. Listing of these RCP does not $constitute\ a\ formal\ pricing\ offer\ from\ Intel.\ Please\ work\ with\ your\ appropriate\ Intel\ representative\ to\ obtain\ a\ formal\ price\ quotation.$

System and Maximum TDP is based on worst case scenarios. Actual TDP may be lower if not all I/Os for chipsets are used.

Low Halogen: Applies only to brominated and chlorinated flame retardants (BFRs/CFRs) and PVC in the final product. Intel components as well as purchased components on the finished assembly meet JS-709 requirements, and the PCB / substrate meet IEC 61249-2-21 requirements. The replacement of halogenated flame retardants and/or PVC may not be better for the environment.

For benchmarking data see http://www.intel.com/performance.

Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different $processor families. See \ http://www.intel.com/content/www/us/en/processors/processor-numbers. html \ for \ details.$

Processors that support 64-bit computing on Intel® architecture require an Intel 64 architecture-enabled BIOS.



Company Information Our Commitment Communities Investor Relations Contact Us Newsroom Jobs













© Intel Corporation | Terms of Use | *Trademarks | Privacy | Cookies | Supply Chain Transparency | Site Map