
KEMET Part Number: PMR210ME6100M100R30

(P410EE104M250AH101)



PMR210, Film, Metallized Paper, Resistor/Capacitor, 0.1 uF, 20%, 1000 VDC, 85°C, Lead Spacing = 25.4mm



Dimensions		
L	30.5mm MAX	
Н	16.1mm MAX	
Т	10.6mm MAX	
S	25.4mm +/-0.4mm	
LL	30mm +5mm	
F	1mm +/-0.05mm	

Packaging Specifications		
Packaging:	Bulk, Bag	
Packaging Quantity:	150	

General Information		
Series:	PMR210	
Dielectric:	Metallized Paper	
Style:	Radial	
Features:	RC Unit approved	
RoHS:	Yes	
Lead:	Wire Leads	
Qualifications:	ENEC, UL, cUL	
AEC-Q200:	No	
Construction:	Molded	
Miscellaneous:	Resistor= 100 Ohms.	
Notes:	Not For New Design, Please Use The New P410 Series @ 300 VAC.	

Specifications		
Capacitance:	0.1 uF	
Capacitance Tolerance:	20%	
Voltage AC:	250 VAC	
Voltage DC:	1000 VDC	
Temperature Range:	-40/+85°C	
Rated Temperature:	85°C	
Insulation Resistance:	3 GOhms	
Safety Class:	X1	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

