


Capacitor, tantalum, 10 uF, 3216, +/-10% Tol, 10V@85C



Dimensions (mm)

Specifications

ID	Dimension	Tolerance	Manufacturer:	KEMET
L	3.2	+/-0.2	Capacitance:	10 uF
W	1.6	+/-0.2	Voltage DC @ 85C:	10V
H	1.6	+/-0.2	Voltage DC @ 105C:	8.5V
F	1.2	+/-0.1	Voltage DC @ 125C:	7V
S	0.8	+/-0.3	Tolerance:	+/-10%
B	0.4	+/-0.15	Application:	General Purpose
X	0.1	+/-0.1	Body Type:	Molded Chip
P	0.4	ref	Temperature Range:	-55/+125C
R	0.4	ref	ESR:	4 Ohm
T	0.13	ref	Footprint:	3216
A	1.4	min	Termination:	Tin
G	1.1	ref	Leakage Current:	1 uA
E	1.3	ref	Dissipation Factor:	6%
			Ripple @ 25C:	0.137 A
			Ripple @ 85C:	0.123 A
			Ripple @ 105C:	0.089 A
			Ripple @ 125C:	0.055 A
			Package Kind:	T&R
			Package Quantity:	9000

Notes:

-In polarity stripe, at KEMET's option, type may be indicated:
 no symbol = Standard MnO2 tantalum chip, O = LowESR
 T494, R = Low ESR T495, F = Fused T496, HT = 150C
 rated T498 (or B45196P, B45198P), H = 175C rated T499,
 M = Multiple anode construction T530 (and B45396R), KO
 = Organic cathode T520 or T521, KT = High temp organic
 cathode T525, KM = Multiple anode organic cathode T530,
 FD= Organic cathode face down terminals T528.