

PRODUCT DATASHEET C15945_STRADA-SQ-T2-B

STRADA-SQ-T2-B

IESNA Type II (medium) beam with minimized house side backlight. Version with location pins.

TECHNICAL SPECIFICATIONS:

Dimensions 25.0 mm

Height 9.1 mm Fastening pin

FasteningpinROHS compliantyes ⁽¹⁾

MATERIAL SPECIFICATIONS:

Component STRADA-SQ-T2-B **Type** Single lens



	Material	Colour	Finish
ns	PMMA	clear	

ORDERING INFORMATION:


Component C15945_STRADA-SQ-T2-B

C15945_STRADA-SQ-T2-B » Box size: 476 x 273 x 292 mm

Qty in box	MOQ	MPQ	Box weight (kg)
2058	294	98	8.5



PRODUCT DATASHEET C15945_STRADA-SQ-T2-B





PRODUCT DATASHEET C15945_STRADA-SQ-T2-B

PHOTOMETRIC DATA (SIMULATED):

CREE ≑		
	XHP70	90* 90*
FWHM	147.0 + 81.0°	75°
Efficiency	94 %	
Peak intensity	0.4 cd/lm	.50*
LEDs/each optic	1	40
Light colour	White	
Required componer		
		200
		30° 15° 1000 15° 30°
	DS	90°
LED	LUXEON M/MX	
FWHM	147.0 + 70.0°	75°
Efficiency	94 %	
Peak intensity	0.7 cd/lm	60 ⁴ 400 60 ⁴
LEDs/each optic	1	
Light colour	White	45* 000 43*
Required componer	ts:	
		\times
		1000
		30* 30*
0.0.0.0.0.0.0		15 ⁵ 1000 15 ⁴
SAMSUI	NG Contraction of the second sec	90* 90*
LED	LH181B	
FWHM	Asymmetric	73° 400 70°
Efficiency	94 %	
Peak intensity	1.3 cd/lm	
LEDs/each optic	1	
Light colour	White	45* 520 65*
Required componer	ts:	
		1000
		\times / \top / λ
		30* 11 ² 2000 ···· 30*
		10 10 10



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Local sales and technical support www.ledil.com/ where_to_buy

Shipping locations Salo, Finland Hong Kong, China

Distribution Partners www.ledil.com/ where_to_buy