

G2-LAURA-RS-P

~8° spot beam. Assembly with thinner white holder, installation tape and location pins.

TECHNICAL SPECIFICATIONS:

Dimensions	21.6 mm
Height	13.1 mm
Fastening	tape, pin
ROHS compliant	yes ⓘ


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
LAURA-RS	Single lens	PMMA	clear	
LAURA-LT-PIN-XP-HLD-WHT	Holder	PC	white	
ROSE-TAPE	Tape	PU tape	black	

ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
CA13628_G2-LAURA-RS-P		360	180	5.9
» Box size:				






PHOTOMETRIC DATA (MEASURED):

CREE

LED XB-H
FWHM 11.0°
Efficiency 91 %
Peak intensity 20.5 cd/Im
LEDs/each optic 1
Light colour White
Required components:





CREE

LED XP-E
FWHM 8.0°
Efficiency 93 %
Peak intensity 33.2 cd/Im
LEDs/each optic 1
Light colour White
Required components:





CREE

LED XP-E2
FWHM 8.0°
Efficiency 91 %
Peak intensity 41.4 cd/Im
LEDs/each optic 1
Light colour White
Required components:



CREE



LED XP-L HD
FWHM 16.0°
Efficiency 90 %
Peak intensity 10.3 cd/Im
LEDs/each optic 1
Light colour White
Required components:





PHOTOMETRIC DATA (MEASURED):





LED XQ-E HI
FWHM 5.0°
Efficiency 94 %
Peak intensity 65.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED LUXEON 3030 2D (Round LES)
FWHM 9.0°
Efficiency 92 %
Peak intensity 22.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON TX
FWHM 11.0°
Efficiency 90 %
Peak intensity 20 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED NCSxx19A
FWHM 10.0°
Efficiency 90 %
Peak intensity 25.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:





PHOTOMETRIC DATA (MEASURED):




LED NVSW219D
FWHM 12.0°
Efficiency 94 %
Peak intensity 15.9 cd/Im
LEDs/each optic 1
Light colour White
Required components:



LED NVSxx19A
FWHM 12.0°
Efficiency 90 %
Peak intensity 17.8 cd/Im
LEDs/each optic 1
Light colour White
Required components:



LED NVSxx19B/NVSxx19C
FWHM 12.0°
Efficiency 90 %
Peak intensity 16.3 cd/Im
LEDs/each optic 1
Light colour White
Required components:





LED PLPVEC2 850A
FWHM 6.0°
Efficiency %
LEDs/each optic 1
Light colour IR
Required components:

PHOTOMETRIC DATA (MEASURED):


SAMSUNG

LED LH351D
FWHM 16.0°
Efficiency 94 %
Peak intensity 9 cd/Im
LEDs/each optic 1
Light colour White
Required components:




SEOUL SEMICONDUCTOR

LED Z5M1/Z5M2
FWHM 11.0°
Efficiency 91 %
Peak intensity 20 cd/Im
LEDs/each optic 1
Light colour White
Required components:



SEOUL SEMICONDUCTOR


LED Z5M3
FWHM 12.0°
Efficiency 94 %
Peak intensity 14.4 cd/Im
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (SIMULATED):




LED	XD16
FWHM	8.6°
Efficiency	93 %
Peak intensity	27 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




LED	XHP35 HD
FWHM	14.0°
Efficiency	94 %
Peak intensity	7.6 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



LED	XHP35 HI
FWHM	12.0°
Efficiency	94 %
Peak intensity	16.1 cd/m
LEDs/each optic	1
Light colour	White
Required components:	




LED	XQ-E HD
FWHM	6.9°
Efficiency	94 %
Peak intensity	44.9 cd/m
LEDs/each optic	1
Light colour	White
Required components:	




PHOTOMETRIC DATA (SIMULATED):




LED LUXEON CZ
FWHM 6.0°
Efficiency 95 %
Peak intensity 54.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED LUXEON Z ES
FWHM 8.0°
Efficiency 95 %
Peak intensity 37.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED NCSxE17A
FWHM 8.0°
Efficiency 95 %
Peak intensity 30.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED NVSxE21A
FWHM 10.0°
Efficiency 94 %
Peak intensity 21.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (SIMULATED):




LED NVSxx19B/NVSxx19C
 FWHM 12.0°
 Efficiency 94 %
 Peak intensity 16.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED OSLO Black
 FWHM 9.5°
 Efficiency 97 %
 Peak intensity 23 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED OSLO Black Flat
 FWHM 6.8°
 Efficiency 94 %
 Peak intensity 48.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED OSLO SSL 150
 FWHM 8.0°
 Efficiency 95 %
 Peak intensity 37.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




PHOTOMETRIC DATA (SIMULATED):

OSRAM

Opto Semiconductors

LED OSLON SSL 80
FWHM 8.0°
Efficiency 95 %
Peak intensity 34.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:




OSRAM

Opto Semiconductors

LED SFH 4770S
FWHM 10.0°
Efficiency 94 %
LEDs/each optic 1
Light colour White
Required components:

SAMSUNG

LED LH351Z
FWHM 10.0°
Efficiency 93 %
Peak intensity 25 cd/lm
LEDs/each optic 1
Light colour White
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)