# ABF.00.250.NTA



## **SUMMARY**

#### # Wires

Coax 1



Image is for illustrative purpose only

Series 00

**Termination type** Coupler/adapter/bridge

IP rating 50

AWG wire size 0.00 - 0.00

Cable Ø 0.00 - 0.00 mm

**Status** active

### **Download**

Request a quote

Catalog

## **TECHNICAL DETAILS**

## **Mechanics**

Shell Style/Model ABF\*: Adapter from LEMO plug to BNC receptacle

Keying Circular, male

Housing Material Brass (nickel plated) shell, collet nut, latch sleeve and mid pieces

Weight 8.17 g

### **Performance**

Configuration 00.250 : 1 Coax (50 Ohm)

Insulator T: PTFE Rated Current 4 Amps

## **Specifications**

Contact Type: Coaxial 50 Ohm Contact Dia.: 0.7 mm (0.03in) Vtest: 2100 V (AC), 3000 V (DC)

Impedance: 50 Ohm VSWR: 1.09 + 0.11 \* f/GHz

### **Others**

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.


Endurance (Shell): >1000 mating cycles

F ret (min): 100 N

Salt Spray Corrosion: >144 hr

## **DRAWINGS**

### **Draws**





### **Dimensions**

	А	L	М
mm.	11.5	36	28
in.	0.45	1.42	1.10

# **RECOMMENDED BY LEMO**

**Tools** 

**Cables** 

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.