



## **SUMMARY**

#### # Wires



Image is for illustrative purpose only

Series 1B

Termination type No contacts / Accessory

IP rating (

AWG wire size 0.00 - 0.00

Cable Ø 3.00 - 3.40 mm

**Status** active

#### **Download**

Request a quote

Catalog

## **TECHNICAL DETAILS**

### **Mechanics**

Shell Style/Model GMA\*: Bend relief Grey

**Keying** No keying

Housing Material Thermoplastic polyurethane elastomer(Desmopan 786)

**Variant** G: Grey

Weight .82 g

### **Performance**

Configuration

Insulator G: PEEK/Pehd

**Rated Current** 


#### **Others**

Temp (min / max):  $-40^{\circ}$ C /  $+80^{\circ}$ C

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

## **DRAWINGS**

#### **Draws**



No keying

### **Dimensions**

	Α	L
mm.	3	30
in.	0.12	1.18

# **RECOMMENDED BY LEMO**

**Tools** 

**Cables** 

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.