

SUMMARY

Wires

Low voltage 30



Image is for illustrative purpose only

| | |
|------------------|--------------------------------|
| Series | 3M |
| Termination type | Female print PCB |
| IP rating | 68 |
| AWG wire size | 22.00 - 22.00 |
| Cable Ø | 0.00 - 0.00 mm |
| Status | active |
| Matching parts | FMN.3M.330.XLC |

Download

[Request a quote](#)
[PCB Eagle Pattern](#)
[PCB Altium Pattern](#)
[PCB KiCad Pattern](#)
[Catalog](#)

TECHNICAL DETAILS

Mechanics

| | |
|-------------------|--|
| Shell Style/Model | HE*: Fixed receptacle, nut fixing for printed circuit, watertight |
| Keying | 3 keys (beta=165, gamma=30, plug: male contacts, receptacle: female contacts) |
| Housing Material | Aluminium (nickel plated, anthracite color) shell and nut, other pieces bronze/brass |
| Variant | P : Watertight |
| Weight | 11.45 g |

Performance

| | |
|---------------|-------------------------|
| Configuration | 3M.330 : 30 Low Voltage |
| Insulator | L: PEEK |
| Rated Current | 3.5 Amps |

Specifications

Contact Type: Print (straight)
Contact Dia.: 0.7 mm (0.028in)
R (max): 6.1 mOhm
Test voltage (kV rms) Contact-contact: 1.10
Test voltage (kV rms) Contact-shell: 1.00


Others

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Endurance (Shell): 3000 mating cycles
Temp (min / max): -20°C / +80°C
Humidity (max): 21 days at 95%
Gunfire vibration: 25 Hz - 2000 Hz, 3 axis (Apache helicopter)
Vibration-Sine: 30 g, 3 axes, 12 hr [10 Hz - 2000 Hz]
Vibration-Random: 37.8 g rms - 3 axes, 4 hr amb [50 Hz - 2000 Hz]
Shock Resistance: 300 g [3 ms]
Lighting strike EIA 364-75: 10K amps - 6 times
Thermal shock: 5 cycles: -65°C to +150°C
EMI Shielding EIA 364-66A: >= 80 dB (1 GHz), >=70 dB (3 GHz), >= 58 dB (6 GHz), >= 40 dB (10 GHz)
Salt Spray Corrosion: max. 48 hr

DRAWINGS

Draws



Dimensions

| | A | C | E | H | Lr | Ls | N | P | R | S1 | S2 | e |
|-----|------|------|------|-------|------|------|------|------|------|------|------|----------|
| mm. | 23 | 22.8 | 5 | 10.16 | 21 | 20.8 | 16.8 | 5.3 | 13.8 | 17.5 | 20 | M19x1.00 |
| in. | 0.91 | 0.90 | 0.20 | 0.40 | 0.83 | 0.82 | 0.66 | 0.21 | 0.54 | 0.69 | 0.79 | |

RECOMMENDED BY LEMO

Tools

Spanner wrench: [DCM.65.000.4PA](#)

LEMO products and services are provided “as is”. LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.