



DESCRIPTION

The **PDV-P9001** are (CdS), Photoconductive photocells designed to sense light from 400 to 700 nm. These light dependent resistors are available in a wide range of resistance values. They're packaged in a two leaded plastic-coated ceramic header

RELIABILITY

This API high-reliability detector is in principle able to meet military test requirements (Mil-STD-750, Mil-STD-883) after proper screening and group test. Contact API for recommendations on specific test conditions and procedures.

FEATURES

- Visible light response
- Sintered construction
- Low cost

APPLICATIONS

- Camera exposure
- Shutter controls
- Night light Controls

ABSOLUTE MAXIMUM RATINGS

$T_a = 23^\circ\text{C}$ non condensing 1/16 inch from case for 3 seconds max

PARAMETER	MIN	MAX	UNITS
Applied Voltage	-	150	V
Continuous Power Dissipation	-	125	mW/°C
Operating and Storage Temperature	-25	+75	°C
Soldering Temperature*	-	+260	°C

OPTO-ELECTRICAL PARAMETERS

T_a = 23°C unless noted otherwise

CHARACTERISTIC	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Dark Resistance	After 10 sec. @ 10 Lux @ 2856 °K	0.3	-	-	MΩ
Illuminated Resistance	10 Lux @ 2856 °K	4	-	11	KΩ
Sensitivity	$\frac{\text{LOG}(R100)-\text{LOG}(R10)**}{\text{LOG}(E100)-\text{LOG}(E10)***}$	-	0.65	-	Ω/Lux
Spectral Application Range	Flooded	400	-	700	nm
Spectral Application Range	Flooded	-	570	-	nm
Rise Time	10 Lux @ 2856 °K	-	60	-	ms
Fall Time	After 10 Lux @ 2856 °K	-	25	-	ms
		-			

TYPICAL PERFORMANCE

CELL RESISTANCE vs. ILLUMINANCE

