



## 8952




**8952-0-05-XX-00-00-03-0**  
Square press-fit in .087 plated thru hole

## 8953




**8953-0-05-XX-00-00-03-0**  
Square press-fit in .047 plated thru hole

## 7310




**7310-0-01-XX-00-00-08-0**  
Board edge press-fit

## 8816




**8816-0-00-XX-00-00-03-0**  
Press-fit in .057 mounting hole

## 8940




**8940-0-00-XX-00-00-03-0**  
Press-fit in .057 mounting hole

## 8876



**8876-0-00-XX-00-00-03-0**  
Press-fit in .057 mounting hole

## 3120



**3120-X-00-XX-00-00-08-0**  
Swage mount in .034 mounting hole

| Basic Part Number | Length A |
|-------------------|----------|
| 3120-1            | .205     |
| 3120-2            | .250     |

## SPECIFICATIONS

**PIN MATERIAL:**  
Brass Alloy 360, 1/2 Hard  
(Except Swage pins which are annealed)

**DIMENSION IN INCHES**  
**TOLERANCES ON:**  
LENGTHS:  $\pm .005$   
DIAMETERS:  $\pm .002$   
ANGLES:  $\pm 2^\circ$

**ORDER CODE: XXXX - X - XX - XX - 00 - 00 - 0X - 0**

**BASIC PART #**

**SPECIFY PIN FINISH:**

- 01 200 $\mu$ " TIN/LEAD OVER NICKEL
- 80 200 $\mu$ " TIN OVER NICKEL  $\diamond$
- 15 10 $\mu$ " GOLD OVER NICKEL  $\diamond$
- 21 20 $\mu$ " GOLD OVER NICKEL  $\diamond$
- 34 50 $\mu$ " GOLD OVER NICKEL  $\diamond$

