

This document was generated on 07/17/2020

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0783730001

Status: **Active**

DDR3 DIMM Sockets Overview:

Description: 1.00mm Pitch DDR3 DIMM Socket, 25° Angle, Through Hole, with Beveled Metal Pins,

Black Housing and Latches, 0.76µm Gold (Au) Plating, 2.79mm Solder Tail Length,

1.57mm PCB Thickness, 1.5V Center Voltage Key, 240 Circuits

Documents:

3D Model Product Specification PS-78373-001-001 (PDF)

3D Model (PDF) RoHS Certificate of Compliance (PDF)

Drawing (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family Memory Module Sockets

Series 78373 Component Type Socket JEDEC Outline MO-269

Overview **DDR3 DIMM Sockets Product Name** DDR3 DIMM

UPC 883906206697

Physical

Material - Metal

Circuits (Loaded) 240 Circuits (maximum) 240 Durability (mating cycles max) 25 **Entry Angle** 25° Anale Flammability 94V-0 **Housing Color** Black Keying to Mating Part Yes Latch Color Black

Copper Alloy Material - Plating Mating Gold Material - Plating Termination

Material - Resin High Temperature Thermoplastic

Net Weight 11.547/g PC Tail Length 2.79mm PCB Locator Yes **PCB** Retention Yes PCB Thickness - Recommended 1.57mm Packaging Type Tray Pitch - Mating Interface 1.00mm Pitch - Termination Interface 1.00mm Plating min - Mating 0.762µm Plating min - Termination 2.540µm Temperature Range - Operating -55° to +85°C Termination Interface: Style Through Hole

Electrical


Current - Maximum per Contact 1.0A

Voltage - Maximum 30V AC (RMS)/DC

Voltage Key Center

Solder Process Data

Duration at Max. Process Temperature (seconds) 010



EU ELV

Not Relevant

EU RoHS China RoHS

Compliant **REACH SVHC** Not Contained Per -D(2020)4578-DC (25 June 2020)

Halogen-Free

Status

Not Low-Halogen

For more information, please visit Contact US

China ROHS Green Image ELV Not Relevant RoHS Phthalates Not Contained

Search Parts in this Series

78373 Series

Mates With

JEDEC Standard 1.27mm Modules

SMC&WAVE

Lead-freeProcess Capability
Max. Cycles at Max. Process Temperature 002 Process Temperature max. C 260

Material Info

Reference - Drawing Numbers Electrical Model Document

EE-78373-001, EE-78373-002

Product Specification PS-78373-001-001

S-Parameter Model SP-78373-001, SP-78373-002

Sales Drawing SD-78373-001

This document was generated on 07/17/2020

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION