

A = 32 STANDARD CONTACTS	L = 3
C = 32 STANDARD CONTACTS	L = 3
S = 64 TOTAL NUMBER OF CONTACTS	

MARKING	STANDARD
PERFORMANCE LEVEL	G/O = CONTACT AREA LEVEL / TERMINATION TIN
FLUX PROOF	NO
FIXING CLIP	NO
DIMENSIONS	SD-85003-0001 SHT 1

C	G1/0	c1-32
A	G1/0	a1-32
CONTACT SYMBOL	PERFORMANCE LEVEL	CONTACT POSITION NUMBER

EC NO. 2004-XXXX DRAWN N.S. 09/09/03 CHK. G.L. 09/09/03 APPR. G.L. 09/09/03	DESCRIPTION MAJOR CRITICAL	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	SCALE	DESIGN UNITS mm INCH	 THIRD ANGLE PROJECTION mm INCH mm ONLY	DIMENSIONS mm INCH mm ONLY	SHT. REV. REVISE ON CAD ONLY
			mm INCH	DRAWN BY & DATE S.S. 14/09/1999	TITLE: 64 POS MALE CONNECTOR ACCORDING DIN 4162 STYLE C CONTACTS ARRANGEMENT  MOLEX INCORPORATED	MATERIAL NO. DRAWING NO. SD-85003-0610 SD-85003-0610	SHEET NO. 1 OF 1	
		4 PLACES ± 0.1 $\pm$	CHECKED BY & DATE G.L. 14/09/1999					
		3 PLACES ± 0.05 $\pm$	APPROVED BY & DATE G.L. 14/09/1999					
		2 PLACES ± 0.1 $\pm$						
		1 PLACE ± 0.15 $\pm$						
		ANGULAR $\pm 2^\circ$						
REV			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.				SIZE D