

BNX005-11










Appearance & Shape









Features

The block type "EMIFIL" BNX series incorporates through-type capacitor, monolithic chip capacitors and bead. The BNX is high performance for use in DC power circuits.

Features

- 1. The filter enables obtaining high insertion loss in wide frequency ranges from 0.5MHz to 1GHz.
- 2. Effective for impulse noise such as electrostatic discharge or spike noise.
- 3. There are no connection routes in the current circuits, thus ensuring highly reliable performance.

Applications

- 1. Displays (PDP/LCD-TV)
- 2. Digital AV equipment
- 3. Amusement equipment
- 4. PC peripheral equipment
- 5. Industry equipment

Packaging Information

| Packaging | Specifications | Minimum Order Quantity |
|-----------|----------------|---------------------------|
| - | Вох | 100 |

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





BNX005-11



| Shape | Lead | |
|-----------------------------|---|--|
| Length | 12.0mm | |
| Length Tolerance | ±0.5mm | |
| Width | 11.0mm | |
| Width Tolerance | ±0.5mm | |
| Thickness | 13.0mm | |
| Thickness Tolerance | max. | |
| Rated Current | 15A | |
| Operating Temperature Range | -40°C to 85°C | |
| Mass(typ.) | 3.3g | |
| Rated Voltage | 50Vdc | |
| Withstanding Voltage | 125Vdc | |
| Insulation Resistance(min.) | 100ΜΩ | |
| Insertion Loss | 1MHz to 1GHz:40dB min. (Line impedance=50Ω) | |

2 of 3

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.






BNX005-11







Insertion Loss Characteristics

Equivalent Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

