





<div>MVF60NN10CMK40 Information</div> <div> <div> <div>▶ General Information</div> <div>▶ Package Information</div> <div>▶ Environmental and Compliance Information</div> <div>▶ Manufacturing Information</div> <div>▶ Ordering Information</div> <div>▶ Operating Characteristics</div> <div>▶ Reliability Data Lookup</div> </div> </div>	
General Information	
Parameter	Value
Part Number	MVF60NN10CMK40
Description	1M Switch USB A5/M4/L2
Product Line	GDLD701
PTI	MBLF
Material Type	Tested Packaged Device
Life Cycle Description (code)	REMOVED FROM ACTIVE PORTFOLIO
Status	No Longer Manufactured
Application/Qualification Tier	10-YEARS APPLICATION LIFE
Package Information	
Parameter	Value
Package Description and Mechanical Drawing	MAP 364 17*17*1.5 P0.8
Device Weight(g)	1.38960
Package Length (nominal)(mm)	17.000
Package Width (nominal)(mm)	17.000
Package Thickness (nominal)(mm)	1.500
Tape & Reel	No
Environmental and Compliance Information	
Parameter	Value
Pb-Free	
RoHS Compliant	
Halogen Free	Yes
Material Composition Declaration (MCD)	Download MCD Report  Download MCD Report 
RoHS Certificate of Analysis (CoA)	Contact Us
2nd Level Interconnect	e1
Moisture Sensitivity Level (MSL)	3
Floor Life	168 HOURS
Peak Package Body Temperature (PPT)(°C)	260
Maximum Time at Peak Temperature (s)	40
Number of Reflow Cycles	3
REACH SVHC	Freescale REACH Statement
UL94 (plastics flammability test)	V0: Burning stops within 10 seconds on a vertical specimen; no drips allowed
Manufacturing Information	
Parameter	Value
Micron Size(?m)	.04
Ordering Information	
Parameter	Value
Exempt from Minimum Delivery Value	Yes
Export Control Classification Number (US)	5A002A
Harmonized Tariff (US) Disclaimer	8542.31.0000
CCATS Document	-
ENC Status	-
Other Trade Compliance Documents	-
Budgetary Price excluding tax(US\$) Change Currency	-
Order	
Operating Characteristics	
Parameter	Value
Sample Exception Availability	N
Reliability Data Lookup	
Downloaded from Arrow.com	