

Introduction  
General purpose  
High-voltage-type  
Multi-contact pair  
(2a, 2b, and 1a1b)  
High-current and  
low-ON-resistance  
Small and high-  
high-dielectric-  
strength  
High-dielectric-  
strength  
Current-limiting  
Low-voltage-capacitance  
and low-ON-resistance  
Small and high-  
voltage  
Certified Models with  
standards derivation

# G3VM-21LR

MOS FET Relays SSOP, Low-output-capacitance and Low-ON-resistance Type (with Low C × R)

## MOS FET Relays in SSOP packages that achieve a low C × R

- Load voltage: 20 V
- G3VM-21LR: Low C × R = 5 pF·Ω, C<sub>OFF</sub> (standard) = 1 pF, R<sub>ON</sub> (standard) = 5 Ω
- G3VM-21LR10: Low C × R = 2.4 pF·Ω, C<sub>OFF</sub> (standard) = 0.8 pF, R<sub>ON</sub> (standard) = 3 Ω
- G3VM-21LR1: Low C × R = 4 pF·Ω, C<sub>OFF</sub> (standard) = 5 pF, R<sub>ON</sub> (standard) = 0.8 Ω
- G3VM-21LR11: Low C × R = 7.2 pF·Ω, C<sub>OFF</sub> (standard) = 40 pF, R<sub>ON</sub> (standard) = 0.18 Ω

RoHS Compliant

### Application Examples


- Semiconductor test equipment
- Communication equipment
- Test & Measurement equipment
- Data loggers



Note: The actual product is marked differently from the image shown here.

### Package (Unit : mm, Average)

SSOP 4-pin



Note: The actual product is marked differently from the image shown here.

### Model Number Legend

G3VM-□□□□□  
1 2 3 4 5

- 1. Load Voltage 2. Contact form 3. Package
- 2: 20 V 1: 1a (SPST-NO) L: SSOP 4-pin

- 4. Additional functions 5. Other informations
- R: Low ON resistance When specifications overlap, serial code is added in the recorded order.

### Ordering Information

Package	Contact form	Terminals	Load voltage (peak value) *	Continuous load current (peak value) *	Tape cut packaging		Tape packaging	
					Model	Minimum package quantity	Model	Minimum package quantity
SSOP4	1a (SPST-NO)	Surface-mounting Terminals	20 V	160 mA	G3VM-21LR	1 pc.	G3VM-21LR(TR05)	500 pcs.
				200 mA	G3VM-21LR10		G3VM-21LR10(TR05)	
				450 mA	G3VM-21LR11		G3VM-21LR11(TR05)	
				900 mA	G3VM-21LR11		G3VM-21LR11(TR05)	

\* The AC peak and DC value are given for the load voltage and continuous load current.  
Note: To order tape packaging for Relays with surface-mounting terminals, add "(TR05)" to the end of the model number.  
Tape-cut SSOPs are packaged without humidity resistance. Use manual soldering to mount them. Refer to common precautions.

### Absolute Maximum Ratings (Ta = 25°C)

Item		Symbol	G3VM-21LR	G3VM-21LR10	G3VM-21LR1	G3VM-21LR11	Unit	Measurement conditions
Input	LED forward current	I <sub>F</sub>	50	30	50	50	mA	Ta ≥ 25°C
	LED forward current reduction rate	ΔI <sub>F</sub> /°C	-0.5	-0.3		-0.5	mA/°C	
	LED reverse voltage	V <sub>R</sub>		5			V	
	Connection temperature	T <sub>J</sub>		125			°C	
	Load voltage (AC peak/DC)	V <sub>OFF</sub>		20			V	
Output	Continuous load current (AC peak/DC)	I <sub>O</sub>	160	200	450	900	mA	
	ON current reduction rate	ΔI <sub>O</sub> /°C	-1.6	-2.0	-4.5	-12	mA/°C	G3VM-21LR11 : Ta ≥ 50°C Others : Ta ≥ 25°C
	Pulse ON current	I <sub>OP</sub>	480	600	1,350	2,700	mA	t=100 ms, Duty=1/10
	Connection temperature	T <sub>J</sub>		125			°C	
	Dielectric strength between I/O (See note 1.)	V <sub>I-O</sub>		1500			V <sub>RMS</sub>	AC for 1 min
Ambient operating temperature		T <sub>a</sub>		-20 to +85			°C	With no icing or condensation
Ambient storage temperature		T <sub>stg</sub>		-40 to +125			°C	
Soldering temperature		-		260			°C	10 s

Note: 1. The dielectric strength between the input and output was checked by applying voltage between all pins as a group on the LED side and all pins as a group on the light-receiving side.

Introduction

General purpose

High-side-voltage

Multi-voltage (2A, 2A, and 1A)

High-current and Low-ON-resistance

Small and high-inductive-switching

High-electric-strength

Current-limiting

Low-voltage and Low-ON-resistance

Small and High-load-voltage

Certified meets RoHS Standards verification

DIP

SOP

SSOP

USOP

VSON

G3VM-21LR


# G3VM-21LR

MOS FET Relays

## Electrical Characteristics (Ta = 25°C)

Item		Symbol	G3VM-21LR	G3VM-21LR10	G3VM-21LR1	G3VM-21LR11	Unit	Measurement conditions	
Input	LED forward voltage	Minimum	1.0	1.15	1.0		V	G3VM-21LR10 : If=5 mA G3VM-21LR/21LR1/21LR11 : If=10 mA	
		Typical	1.15	1.35	1.15				
		Maximum	1.3	1.45	1.3				
	Reverse current	Ir	Maximum	10				μA	VR=5 V
	Capacitance between terminals	Ct	Typical	15	70	15		pF	V=0, f=1 MHz
Output	Trigger LED forward current	I <sub>FT</sub>	Maximum	4	3	4	3	mA	I <sub>o</sub> =100 mA
	Release LED forward current	I <sub>FC</sub>	Minimum	0.2	0.1	0.2	0.1	mA	I <sub>OFF</sub> =10 μA
	Maximum resistance with output ON	R <sub>ON</sub>	Typical	5	3	0.8	0.18	Ω	G3VM-21LR/21LR1 : If=5 mA, I <sub>o</sub> =Continuous load current ratings, t=10 ms G3VM-21LR10/21LR11 : If=5 mA, I <sub>o</sub> =Continuous load current ratings, t<1 s
			Maximum	8	5	1.2	0.22		
	Current leakage when the relay is open	I <sub>LEAK</sub>	Typical	–	0.01	–		nA	G3VM-21LR/21LR1: V <sub>OFF</sub> =20 V, T <sub>a</sub> =50°C G3VM-21LR10/21LR11 : V <sub>OFF</sub> =20 V
			Maximum	1	0.2	1			
	Capacitance between terminals	C <sub>OFF</sub>	Typical	1	0.8	5	40	pF	G3VM-21LR10 : V=0, f=100 MHz G3VM-21LR/21LR1/21LR11 : V=0, f=100 MHz, t<1 s
			Maximum	2.5	1.1	12	–		
Capacitance between I/O terminals	C <sub>I-O</sub>	Typical	0.8	0.3	0.8	0.3	pF	f=1 MHz, V <sub>S</sub> =0 V	
Insulation resistance between I/O terminals	R <sub>I-O</sub>	Minimum	1000				MΩ	V <sub>I-O</sub> =500 VDC, RoHs=60%	
		Typical	10 <sup>9</sup>						
Turn-ON time	t <sub>ON</sub>	Typical	0.06	–	0.2	0.3	ms	If=5 mA, R <sub>L</sub> =200 Ω, V <sub>DD</sub> =10 V (See note 2.)	
		Maximum	0.5	0.2	0.5	2			
Turn-OFF time	t <sub>OFF</sub>	Typical	0.12	–	0.2				
		Maximum	0.5	0.2	0.5	1			

Note: 2. Turn-ON and Turn-OFF Times



## Recommended Operating Conditions

For usage with high reliability, Recommended Operation Conditions is a measure that takes into account the derating of Absolute Maximum Ratings and Electrical Characteristics.

Each item on this list is an independent condition, so it is not simultaneously satisfy several conditions.


Item	Symbol	G3VM-21LR	G3VM-21LR10	G3VM-21LR1	G3VM-21LR11	Unit
Load voltage (AC peak/DC)	V <sub>DD</sub>	Maximum	20			V
Operating LED forward current	I <sub>F</sub>	Minimum	10	–	10	–
		Maximum	30	20	30	20
Continuous load current (AC peak/DC)	I <sub>O</sub>	Maximum	160	200	450	900
Ambient operating temperature	T <sub>a</sub>	Minimum	–20			°C
		Maximum	60			

## Spacing and Insulation


Item	Minimum	Unit
Creepage distances	2.5	mm
Clearance distances	2.5	
Internal isolation thickness	0.1	

## Engineering Data


### LED forward current vs. Ambient temperature




### Continuous load current vs. On-state voltage




### Trigger LED forward current vs. Ambient temperature




### Continuous load current vs. Ambient temperature




### On-state resistance vs. Ambient temperature




### Turn ON, Turn OFF time vs. LED forward current




### LED forward current vs. LED forward voltage



### G3VM-21LR11



### G3VM-21LR10/21LR11




# G3VM-21LR□

## MOS FET Relays


### Engineering Data

#### ● Turn ON, Turn OFF time vs. Ambient temperature G3VM-21LR/21LR1




#### ● Current leakage vs. Load voltage


G3VM-21LR/21LR1




G3VM-21LR10/21LR11




G3VM-21LR11



#### ● Current leakage vs. Ambient temperature G3VM-21LR10



#### ● Output terminal capacitance vs. Load voltage G3VM-21LR/21LR1/21LR11



Introduction  
General purpose  
High-voltage type  
Multi-contact pair (2a, 2b, and 1a1b)  
High-current and Low-ON-resistance  
Small and High-dielectric strength  
High-dielectric strength  
Current-limiting  
Low-voltage, capacitive and Low-ON-resistance  
Small and High-voltage  
Certified Models with Standards Certification  
DIP  
SOP  
SSOP  
USOP  
VSON


# G3VM-21LR□

MOS FET Relays

## ■Appearance / Terminal Arrangement / Internal Connections

### ●Appearance

**SSOP (Shrink Small Outline Package)**  
SSOP 4-pin




- Note: 1.** The actual product is marked differently from the image shown here.  
**Note: 2.** "G3VM" does not appear in the model number on the Relay.

\* Actual model name marking for each model

Model	Marking
G3VM-21LR	210
G3VM-21LR10	21A
G3VM-21LR1	211
G3VM-21LR11	21B

### ●Terminal Arrangement/ Internal Connections (Top View)




## ■Dimensions (Unit: mm)




### Surface-mounting Terminals

Weight: 0.03 g



Unless otherwise specified, the dimensional tolerance is  $\pm 0.1$  mm.

### Actual Mounting Pad Dimensions (Recommended Value, TOP VIEW)



**Note:** The actual product is marked differently from the image shown here.

## ■Approved Standards

UL recognized

Approved Standards	Contact form	File No.
UL (recognized)	1a (SPST-NO)	E80555

## ■Safety Precautions

- Refer to the *Common Precautions for All MOS FET Relays* for precautions that apply to all MOS FET Relays.