

Home > Product Information > Product category > Relay > Printed circuit board relay > Signal relay > G6A > List of models > **G6A-274P DC24**

Mini relay

G6A-274P DC24

Japanese

Open a print page



Image

Standard type, Crossbar / Twin, Terminal for printed circuit board, DC30V 2A (Resistive load), AC125V 0.5A (Resistive load), Output 2c (2A 30V)

Coil rating	DC24V 8.3mA
Contact configuration	2c
Contact mechanism	Crossbar Twin
Contact material	Au alloy + Ag
Contact rated load	AC125V 0.5A (Resistive load) AC125V 0.3A (Inductive load (cos ϕ = 0.4)) DC30V 2A (Resistive load) DC30V 1A (Inductive load (L / R = 7ms))
Terminal structure	Printed circuit board terminal

▶ G6A format list

Rating / performance

Information update: 2019/02/26

Rated

Product classification	Standard type single stable relay monostable	
Protective structure	Plastic seal type	
Terminal structure	Printed circuit board terminal	
coil	Coil rating	DC24V 8.3mA
	Coil resistance	2880 Ω
	Operating voltage (set voltage)	70% or less
	Return voltage (reset voltage)	More than 10
	Maximum allowable voltage	200% (23 ° C)
	power consumption	About 200mW
contact	Rated load	AC125V 0.5A (Resistive load) AC125V 0.3A (Inductive load (cos ϕ = 0.4)) DC30V 2A (Resistive load) DC30V 1A (Inductive load (L / R = 7ms))
	Maximum value of contact voltage	AC250V DC220V
	Maximum value of contact current	AC: 2A (Resistive load) AC: 1A (Inductive load (cos ϕ = 0.4)) DC: 2A (Resistive load) DC: 1A (Inductive load (L / R = 7ms))
	Contact configuration	2c
	Contact mechanism	Crossbar Twin
	Contact material	Au alloy + Ag

Performance

Contact resistance	50mΩ or less (DC1V 10mA voltage drop method)
Operating time	5 ms or less
Recovery time	3 ms or less
Insulation resistance	Between coil and contact: 1000 MΩ or more (DC500 V insulation resistance meter) Between different pole contacts: 1000 MΩ or more (DC 500 V insulation resistance meter) Between same pole contacts: 1000 MΩ or more (DC 500 V insulation resistance meter)
Withstand voltage	Between coil and contact: AC1000V 50 / 60Hz 1min Between different pole contacts: AC1000V 50 / 60Hz 1min Between same pole contacts: AC1000V 50 / 60Hz 1min
Vibration resistant (durable)	10 to 55 to 10 Hz Single amplitude 2.5 mm (Double amplitude 5 mm)
Vibration resistance (malfunction)	10 to 55 to 10 Hz Single amplitude 1.65 mm (Double amplitude 3.3 mm)
Impact resistant (durable)	1000 m / s ** 2
Shock resistance (malfunction)	500 m / s ** 2
durability	Mechanical: 100 million times or more (switching frequency 36,000 times / h) Electrical: 500,000 times or more (rated load, switching frequency 1,800 times / h)
failure rate	DC10mV 10 μ A (P level, reference value) (switching frequency 60 times / min)
Operating temperature limit	-40 to 70 ° C (with no icing or condensation)
Operating humidity range	5 to 85% RH (with no icing or condensation)
mass	Approximately 3.5 g

Information update: 2019/02/26

オムロンFASTストア View Cart (0)

Shape · Series



Mini relay
G6A

catalog

About this form

I-Web 探す I-Web 探す

Add to My Parts

add to cart

Delivery date division

Standard stock

Sales price, special price, and delivery date will be the information in OMRON FA store.

Environmental and safety measures

Find RoHS / REACH compliance

I-Web 探す status

Confirm export non-determination

I-Web 探す I-Web 探す

Inquire

Selection, operation, setting method, etc.

Page top

Notice / Latest Information

solution

Manufacturing site innovation
Event publication
Field data utilization service i-BELT

Products Supporting i-Automation!
Panel Solution (Control Panel)

product

Sensor
switch
Safety
relay
Control
FA system equipment
Motion / drive
Robotics
Energy saving support / Environmental measures equipment
Power supply / peripheral equipment etc

Technical Guide

Product FAQ
Technical explanation
FA glossary

Download center

catalog
manual
2D CAD
3D CAD
Electrical control CAD
software

Service support

Robotics support
Japanese Counseling Desk
Japan Desk
World Regional Service Information

Semina

Choose from the course (FA practice seminar)
Choose from the course (e-learning)
Choose from the venue
Introductory course for new employees
Designer Introductory Course
Introductory course for maintainers

Sales network

Domestic sales network
Overseas sales network

online store

Related information

Format Name Index
Selection by purpose and specification
Improvement / utilization casebook
Discontinued product / Recommended replacement product
Catalog / Manual correction
Video channel
Export not judged
Standard certification / conformity
RoHS / REACH compliant
Usage notes
Test machine rental
Special page

OMRON Corporation | help | site map | Related Links | About the handling of personal information | Terms of use | Product acceptance terms | Facebook

© Copyright OMRON Corporation 1996-2019. All Rights Reserved.

Downloaded from Arrow.com