





CAD Data

mm inch



FEATURES

1. Micro-miniature package (SSOP) using a new flat lead terminal shape
 Compared to previous models (SOP 4-pin), mounting area can be reduced by approximately 56%*. This contributes to improved output signal transit characteristics.



*Comparison of area of SSOP and SOP 4-pin (including leads).

2. Full lineup with C×R10
 Lineup includes three types with superior electrical performance of C×R10. R type and C type, respectively, feature greatly reduced on resistance and output capacitance.

		On resistance (Typical)	Output capacitance (Typical)
R type	AQY221R4V	0.55Ω	24pF
	AQY221R2V	0.75Ω	12.5pF
C type	AQY221N2V	9.5Ω	1.0pF

TYPICAL APPLICATIONS

- 1. Measuring and testing equipment**
Semiconductor testing equipment, Probe cards, Datalogger, Board tester and other testing equipment
- 2. Telecommunication and broadcasting equipment**
- 3. Medical equipment**

TYPES

	Type	Output rating*1		Package	Tape and reel packing style*2		Packing quantity in tape and reel
		Load voltage	Load current		Picked from the 1 and 4-pin side	Picked from the 2 and 3-pin side	
AC/DC dual use	Low on-resistance (R type)	40 V	500 mA	SSOP	AQY221R4VY	AQY221R4VW	3,500 pcs.
		40 V	250 mA		AQY221R2VY	AQY221R2VW	
	Low capacitance (C type)	40 V	120 mA		AQY221N2VY	AQY221N2VW	

Notes: *1 Indicate the peak AC and DC values.

*2 Tape and reel is the standard packing style for SSOP.

For space reasons, the three initial letters of the part number "AQY", the package (SSOP) indication "V", and the packaging style "Y" or "W" are not marked on the relay. (Ex. the label for product number AQY221R4VY is 221R4)

*3 Types with a built-in resistor.

RATING

1. Absolute maximum ratings (Ambient temperature: 25°C 77°F)

Item	Symbol	R type		C type	Remarks
		AQY221R4V	AQY221R2V	AQY221N2V	
Input	LED forward current	50mA			
	LED reverse voltage	5V			
	Peak forward current	1A			f=100 Hz, Duty factor=0.1%
	Power dissipation	75mW			
Output	Load voltage (peak AC)	40V			
	Continuous load current	0.5A	0.25A	0.12A	Peak AC, DC
	Peak load current	1A	0.75A	0.3A	100ms (1shot), V _L =DC
	Power dissipation	250mW			
Total power dissipation	P _T	300mW			
I/O isolation voltage	V _{iso}	1,500V AC			
Operating temperature	T _{opr}	-40°C to +85°C -40°F to +185°F			Non-condensing at low temperatures
Storage temperature	T _{stg}	-40°C to +100°C -40°F to +212°F			


RF SSOP 1 Form A CxR10 (AQY221○○V)

2. Electrical characteristics (Ambient temperature: 25°C 77°F)

Item			Symbol	R type		C type	Condition
				AQY221R4V	AQY221R2V	AQY221N2V	
Input	LED operate current	Typical	I _{Fon}	0.9 mA		1.0 mA	AQY221R4V: I _L = 500 mA AQY221R2V: I _L = 250 mA AQY221N2V: I _L = 80 mA
		Maximum		3.0 mA			
	LED turn off current	Minimum	I _{Foff}	0.1 mA		0.2 mA	
		Typical		0.8 mA		0.9 mA	
LED dropout voltage*1	Typical	V _F	1.35 V (1.14 V at I _F = 5 mA)			I _F = 50 mA	
	Maximum		1.5 V				
Output	On resistance	Typical	R _{on}	0.55Ω	0.75Ω	9.5Ω	AQY221R4V: I _F = 5 mA, I _L = 500 mA AQY221R2V: I _F = 5 mA, I _L = 250 mA AQY221N2V: I _F = 5 mA, I _L = 80 mA Within 1 s on time
		Maximum		1Ω	1.25Ω	12.5Ω	
	Output capacitance	Typical	C _{out}	24 pF	12.5 pF	1.0 pF	
		Maximum		30 pF	18 pF	1.5 pF	
Off state leakage current	Typical	I _{Leak}	0.02 nA		0.01 nA	I _F = 0 mA, V _L = Max.	
	Maximum		10 nA				
Transfer characteristics	Turn on time*2	Typical	T _{on}	0.25 ms	0.10 ms	0.20 ms	AQY221R4V: I _F = 5 mA, V _L = 10 V, R _L = 20Ω AQY221R2V: I _F = 5 mA, V _L = 10 V, R _L = 40Ω AQY221N2V: I _F = 5 mA, V _L = 10 V, R _L = 125Ω
		Maximum		0.75 ms	0.5 ms		
	Turn off time*2	Typical	T _{off}	0.08 ms		0.02 ms	
		Maximum		0.2 ms			
	I/O capacitance	Typical	C _{iso}	0.8 pF			
		Maximum		1.5 pF			
Initial I/O isolation resistance	Minimum	R _{iso}	1,000 MΩ			500 V DC	

Note: Variation possible through combinations of output capacitance and on resistance. For more information, please contact our sales office in your area.

*Turn on/Turn off time



RECOMMENDED OPERATING CONDITIONS

Please obey the following conditions to ensure proper relay operation and resetting.

Item	Symbol	Recommended value	Unit
Input LED current	I _F	5	mA

■ Dimensions

■ Schematic and Wiring Diagrams

■ Cautions for Use

■ These products are not designed for automotive use.


If you are considering to use these products for automotive applications, please contact your local Panasonic Electric Works technical representative.

Please refer to our information on [PhotoMOS Relays for Automotive Applications](#).

REFERENCE DATA


1. Load current vs. ambient temperature characteristics

Allowable ambient temperature: -40°C to $+85^{\circ}\text{C}$
 -40°F to $+185^{\circ}\text{F}$




2. Load current vs. Load voltage characteristics

Ambient temperature: 25°C 77°F




3. On resistance vs. ambient temperature characteristics

Measured portion: between terminals 3 and 4
 LED current: 5 mA; Load voltage: 10V (DC)
 Continuous load current: AQY221R4V 500mA (DC),
 AQY221R2V 250mA (DC), AQY221N2V 80mA (DC)




4. Turn on time vs. ambient temperature characteristics

Measured portion: between terminals 3 and 4
 LED current: 5 mA; Load voltage: 10V (DC)
 Continuous load current: AQY221R4V 500mA (DC),
 AQY221R2V 250mA (DC), AQY221N2V 80mA (DC)




5. Turn off time vs. ambient temperature characteristics

Measured portion: between terminals 3 and 4
 LED current: 5 mA; Load voltage: 10V (DC)
 Continuous load current: AQY221R4V 500mA (DC),
 AQY221R2V 250mA (DC), AQY221N2V 80mA (DC)




6. LED operate current vs. ambient temperature characteristics

Measured portion: between terminals 3 and 4
 Load voltage: 10V (DC)
 Continuous load current: AQY221R4V 500mA (DC),
 AQY221R2V 250mA (DC), AQY221N2V 80mA (DC)




7. LED turn off current vs. ambient temperature characteristics

Measured portion: between terminals 3 and 4
 Load voltage: 10V (DC)
 Continuous load current: AQY221R4V 500mA (DC),
 AQY221R2V 250mA (DC), AQY221N2V 80mA (DC)




8. LED dropout voltage vs. ambient temperature characteristics

LED current: 5 to 50 mA



9. Current vs. voltage characteristics of output at MOS portion


Measured portion: between terminals 3 and 4
 Ambient temperature: 25°C 77°F



RF SSOP 1 Form A CxR10 (AQY221○○V)


10. Off state leakage current vs. load voltage characteristics

Measured portion: between terminals 3 and 4
Ambient temperature: 25°C 77°F




11. Turn on time vs. LED forward current characteristics

Measured portion: between terminals 3 and 4
Load voltage: 10V (DC)
Continuous load current: AQY221R4V 500mA (DC), AQY221R2V 250mA (DC), AQY221N2V 80mA (DC)
Ambient temperature: 25°C 77°F




12. Turn off time vs. LED forward current characteristics

Measured portion: between terminals 3 and 4
Load voltage: 10V (DC)
Continuous load current: AQY221R4V 500mA (DC), AQY221R2V 250mA (DC), AQY221N2V 80mA (DC)
Ambient temperature: 25°C 77°F




13. Output capacitance vs. applied voltage characteristics

Measured portion: between terminals 3 and 4
Frequency: 1 MHz, 30m Vrms
Ambient temperature: 25°C 77°F



14. Isolation vs. frequency characteristics (50Ω impedance)

Measured portion: between terminals 3 and 4
Ambient temperature: 25°C 77°F



15. Insertion loss vs. frequency characteristics (50Ω impedance)

Measured portion: between terminals 3 and 4
Ambient temperature: 25°C 77°F

