

## Stacked Metallized PEN Film Chip Capacitor

Type : ECWU(C)

Stacked metallized PEN film as dielectric with simple  
mold-less construction




## ■ Features

- Small in size
- For reflow soldering
- RoHS directive compliant

## ■ Recommended Applications

- General purpose (Coupling, By-pass)

## ■ Explanation of Numbers




## ■ Specification

Category temp. range (Including temperature-rise on unit surface)		- 55 °C to +125 °C			
Rated voltage	100 VDC, 250 VDC, 630VDC (Derating of rated voltage by 1.25% / °C more than 85°C)				
Capacitance range	100 VDC	0.012 µF to 1.0 µF (E12)			
	250 VDC	0.0010 µF to 0.12 µF (E12)			
	630 VDC	0.022 µF, 0.027 µF, 0.033 µF			
Capacitance tolerance	100 VDC	±5 %(J), ±10 %(K) ( C≥0.18 µF ±10 %(K) only)			
	250 VDC	±5 %(J), ±10 %(K)			
	630 VDC	±5 %(J)			
Withstand voltage	Between terminals : Rated volt. (VDC) × 150 % 60 s				
Dissipation factor (tan δ )	tan δ ≤ 1.0 % (20 °C, 1 kHz)				
Insulation resistance (IR)	C≤0.33 µF	100 VDC, 250 VDC, 630 VDC : IR≥3000MΩ (20 °C, 100 VDC, 60 s)			
	C>0.33 µF	100 VDC : IR≥1000 MΩ · µF (20 °C, 100 VDC, 60 s)			
Soldering conditions	100 VDC	Reflow soldering 240°C max. and 60 s max. at more than 220°C (Temp. at cap. surface ) Please consult us for Reflow 250 °C max product.			
	250 VDC				
	630 VDC	Reflow soldering 250°C max. and 60 s to 150s. at more than 217°C (Temp. at cap. surface )			


\*In case of applying voltage in alternating current (50 Hz or 60 Hz sine wave) to a capacitor with DC rated voltage, please refer to the page of "Permissible voltage (R.M.S) in alternating current corresponding to DC rated voltage".

\*Please consult us for capacitance range between 0.15 µF and 1.0 µF(250 VDC)

## ■Construction



## ■Dimensions in mm(not to scale)



\* To be applied only for size Z, Y, X

\*\* To be applied only for size V

\*\*\* To be applied only for size B, Z, Y, X, V

Size code	L	W	H
E1	4.8	3.3	1.4
E2	4.8	3.3	2.0
E3a	4.8	3.3	2.4
E3	4.8	3.3	2.8
D1	6.0	4.1	1.8
D2	6.0	4.1	2.0
D3	6.0	4.1	2.4
D4	6.0	4.1	2.8
D5	6.0	4.1	3.2
B	6.0	5.0	
Z	7.1	5.0	
Y	7.1	6.3	
X	7.7	5.5	
V	9.8	6.3	

※Refer to the column "Rating, Dimensions & Quantity".

## ■Taping Specification for Automatic Mounting

Refer to the taping specification.

## ■Rating, Dimensions & Quantity / Reel

•Capacitance tolerance: ±5 % (J), ±10 % (K)

Cap. (μF)	Rated volt. 100 VDC					Rated volt. 250 VDC						
	Part No.	Dimensions (mm)			Size code	Quantity	Part No.	Dimensions (mm)			Size code	Quantity
		L	W	H				L	W	H		
0.0010							ECWU2102□C9	4.8	3.3	1.4	E1	
0.0012							ECWU2122□C9	4.8	3.3	1.4	E1	
0.0015							ECWU2155□C9	4.8	3.3	1.4	E1	
0.0018							ECWU2182□C9	4.8	3.3	1.4	E1	
0.0022							ECWU2222□C9	4.8	3.3	1.4	E1	
0.0027							ECWU2272□C9	4.8	3.3	1.4	E1	
0.0033		Please use DC100V rating of ECWU(X)					ECWU2332□C9	4.8	3.3	1.4	E1	
0.0039							ECWU2392□C9	4.8	3.3	1.4	E1	
0.0047							ECWU2472□C9	4.8	3.3	1.4	E1	
0.0056							ECWU2562□C9	4.8	3.3	1.4	E1	
0.0068							ECWU2682□C9	4.8	3.3	1.4	E1	
0.0082							ECWU2822□C9	4.8	3.3	1.4	E1	
0.010							ECWU2103□C9	4.8	3.3	1.4	E1	
0.012	ECWU1123□C9	4.8	3.3	1.4	E1		ECWU2123□C9	4.8	3.3	1.4	E1	
0.015	ECWU1153□C9	4.8	3.3	1.4	E1		ECWU2153□C9	4.8	3.3	1.4	E1	
0.018	ECWU1183□C9	4.8	3.3	1.4	E1		ECWU2183□C9	4.8	3.3	2.0	E2	
0.022	ECWU1223□C9	4.8	3.3	1.4	E1		ECWU2223□C9	4.8	3.3	2.0	E2	
0.027	ECWU1273□C9	4.8	3.3	1.4	E1		ECWU2273□C9	4.8	3.3	2.4	E3a	
0.033	ECWU1333□C9	4.8	3.3	1.4	E1		ECWU2333□C9	4.8	3.3	2.8	E3	2,000
0.039	ECWU1393□C9	4.8	3.3	1.4	E1		ECWU2393□C9	6.0	4.1	2.0	D2	3,000
0.047	ECWU1473□C9	4.8	3.3	2.0	E2		ECWU2473□C9	6.0	4.1	2.4	D3	
0.056	ECWU1563□C9	4.8	3.3	2.0	E2		ECWU2563□C9	6.0	4.1	2.8	D4	2,000
0.068	ECWU1683□C9	4.8	3.3	2.4	E3a		ECWU2683□C9	6.0	4.1	3.2	D5	
0.082	ECWU1823□C9	4.8	3.3	2.8	E3		ECWU2823□C9	6.0	5.0	3.2	B	
0.10	ECWU1104□C9	6.0	4.1	1.8	D1		ECWU2104□C9	6.0	5.0	3.8	B	
	ECWU1104V33	4.8	3.3	2.8	E3		ECWU2124□C9	6.0	5.0	4.5	B	1,500
0.12	ECWU1124□C9	6.0	4.1	2.4	D3							
0.15	ECWU1154□C9	6.0	4.1	2.8	D4							
0.18	ECWU1184KC9	7.1	5.0	2.0	Z							
0.22	ECWU1224KC9	7.1	5.0	2.4	Z							
0.27	ECWU1274KC9	7.1	5.0	2.9	Z							
0.33	ECWU1334KC9	7.1	5.0	3.5	Z							
0.39	ECWU1394KC9	7.7	5.5	3.4	X							
0.47	ECWU1474KC9	7.7	5.5	4.0	X							
0.56	ECWU1564KC9	9.8	6.3	3.0	V							
0.68	ECWU1684KC9	9.8	6.3	3.6	V							
0.82	ECWU1824KC9	9.8	6.3	4.3	V							
1.0	ECWU1105KC9	9.8	6.3	5.1	V							

↑ Cap. tol. code


↑ Cap. tol. code

■ Rating, Dimensions & Quantity / Reel

● Capacitance tolerance :  $\pm 5\% (J)$

Cap. ( $\mu F$ )	Part No.	Rated volt. 630 VDC			Quantity	
		Dimensions (mm)				
		L	W	H		
0.022	ECWUC2J223JV	7.1	6.3	3.6	Y	1000
0.027	ECWUC2J273JV	7.1	6.3	4.1	Y	
0.033	ECWUC2J333JV	7.1	6.3	5.1	Y	

■ Recommended for Land Dimensions(mm)




Size code	Land dimensions		
	Reflow soldering		
	A	B	C
E1,E2,E3a,E3	2.6	6.6	3.0
D1,D2,D3,D4,D5	3.8	7.8	3.8
B	3.8	7.8	4.6
Z	4.5	9.0	4.6
Y	4.5	9.0	5.7
X	5.1	9.7	5.0
V	7.2	11.9	5.7

Panasonic






## ECWU (C) Type DC100V series (Stacked Metallized Film)

### Electrical Characteristics < Typical Data >

#### Temperature Characteristics




#### Frequency Characteristics




## ECWU (C) Type DC100V series (Stacked Metallized Film)

### Applicable Specifications


Permissible current




Permissible current



Permissible voltage



Permissible voltage



\* Please consult Panasonic if your condition exceeds the above spec.

\*Permissible voltage graph is the case of sine waveform. When you use this product, peak voltage must not exceed DC rated voltage.

\*The current value (Aop) is calculated using "nominal capacitance." In fact, it changes by the tolerance of a capacitance value, capacitance change, etc.

## ECWU (C) Type DC100V series (Stacked Metallized Film)

### Applicable Specifications


**Pulse Handling Capability (dv/dt)**  
(Max 10000cycles)

Rating Voltage	Capacitance Value(uF)	Code	dv/dt(V/us)	Current( $I_{OP}$ ) (A)
DC 100V	0.012	123	320	3.8
	0.015	123		4.8
	0.018	183		5.8
	0.022	223		7.0
	0.027	273		8.6
	0.033	333		10.6
	0.039	393		12.5
	0.047	473		15.0
	0.056	563		17.9
	0.68	683		21.8
	0.82	823		26.2

**Pulse Handling Capability (dv/dt)**  
(Max 10000cycles)

Rating Voltage	Capacitance Value(uF)	Code	dv/dt(V/us)	Current( $I_{OP}$ ) (A)
DC 100V	0.10	104	120	21.0
	0.12	124		25.2
	0.15	154		31.5
	0.18	184		21.6
	0.22	224		26.4
	0.27	274		32.4
	0.33	334		39.6
	0.39	394		39.0
	0.47	474		47.0
	0.56	564		39.2
	0.68	684	70	47.6
	0.82	824		57.4
	1.0	105		70.0

### Voltage Derating by Temperature



\* Please consult Panasonic if your condition exceeds the above spec.

\*Permissible voltage graph is the case of sine waveform. When you use this product, peak voltage must not exceed DC rated voltage.


\*The current( $I_{OP}$ ) value is calculated using nominal capacitance.

Panasonic






## ECWU (C) Type DC250V series (Stacked Metallized Film)

### Electrical Characteristics < Typical Data >

#### Temperature Characteristics




#### Frequency Characteristics




## ECWU (C) Type DC250V series (Stacked Metallized Film)

### Applicable Specifications


Permissible current




Permissible current



Permissible voltage



Permissible voltage



\* Please consult Panasonic if your condition exceeds the above spec.

\*Permissible voltage graph is the case of sine waveform. When you use this product, peak voltage must not exceed DC rated voltage.

\*The current( $I_{0-P}$ ) value is calculated using nominal capacitance.


## ECWU (C) Type DC250V series (Stacked Metallized Film)

### Applicable Specifications

**Pulse Handling Capability (dv/dt)**  
(Max 10000cycles)

Rating Voltage	Capacitance Value(uF)	Code	dv/dt(V/us)	Current( $I_{OP}$ ) (A)
DC 250V	0.0010	102	615	0.62
	0.0012	122		0.74
	0.0015	152		0.92
	0.0018	182		1.11
	0.0022	222		1.35
	0.0027	272		1.66
	0.0033	332		2.03
	0.0039	392		2.40
	0.0047	472	360	1.69
	0.0056	562		2.02
	0.0068	682		2.45
	0.0082	822		2.95
	0.010	103		3.60
	0.012	123		4.32
	0.015	153		5.40
	0.018	183		6.48
	0.022	223		7.92
	0.027	273		9.72
	0.033	333		11.88

Rating Voltage	Capacitance Value(uF)	Code	dv/dt(V/us)	Current( $I_{OP}$ ) (A)
DC 250V	0.039	393	240	9.36
	0.047	473		11.28
	0.056	563		13.44
	0.068	683		16.32
	0.082	823		19.68
	0.10	104		24.00
	0.12	124		28.80
	0.15	154		28.50
	0.18	184	190	34.20
	0.22	224		41.80
	0.27	274		31.05
	0.33	334		37.95
	0.39	394		44.85
	0.47	474	115	54.05
	0.56	564		36.40
	0.68	684		44.20
	0.82	824		53.30
	1.0	105		65.00



\* Please consult Panasonic if your condition exceeds the above spec.


\*Permissible voltage graph is the case of sine waveform. When you use this product, peak voltage must not exceed DC rated voltage.

\*The current( $I_{OP}$ ) value is calculated using nominal capacitance.




**TYPE:ECWU (C)** DC630V series (Stacked Metallized Film)

**Electrical Characteristics <Typical Data >**



**Temperature Characteristics**




**Frequency Characteristics**




**at DC100V**



### Applicable Specifications



### Voltage Derating by Temperature



### Pulse Handling Capability (dv/dt) (Max 10000cycles)

Rating Voltage	Capacitance Value ( $\mu\text{F}$ )	Code	$\text{dV}/\text{dt}$ (V/ $\mu\text{s}$ )	Current(A <sub>D-P</sub> )
DC 630V	0.022	223	250	5.5
	0.027	273	250	6.7
	0.033	333	250	8.2

\*Please consult Panasonic if your condition exceeds the above

\*Permissible voltage graph is the case of sine waveform. When you use this product, peak voltage must not exceed DC rated voltage.

\*The current(0-P) value is calculated using nominal capacitance.

### 2.4.2 Cautions for use of soldering iron

- Be careful that the soldering irons do not directly touch the main body of the chip film capacitor. In particular, don't touch the side (cut section). If touched by the heated soldering iron, lowering of insulation resistance, shortcircuit or other characteristic deterioration may occur.
- Preheat the printed wiring board land sufficiently with the soldering iron, and then solder. Solder without directly touching the iron tip to the electrode of the capacitor.
- Don't reuse the products once removed by the soldering irons.
- Should not mount the chip film capacitors in the mass production by soldering iron. (The temperature control is difficult, and the characteristics may be deteriorated.)
- Should not resolder with heat directly from bottom side of P. W. Board. because capacitor will likely be damaged.

### 3. Washing the mounted boards

#### <Usable detergent and washing method>

(Usable detergent)

Classification	Detergent name	Maker
Alcohol derivative	IPA (isopropyl alcohol)	(Reagent for general industrial use)
Halogenated hydrocarbon	AK-225AES	Asahi Glass Co.

#### (Washing method)

Condition Item	Temperature	Time
Immersion washing	50 °C	Within 5 minutes
Steam washing	50 °C	Within 5 minutes
Ultrasonic washing	50 °C	Within 5 minutes

#### <CFC substitute detergent>

As a result of regulation of CFC and chlorine derivative detergents, many substitute detergents come to be used, but the performance of the chip type capacitor may be reduced depending on the type of detergent or washing condition. Check sufficiently beforehand. Consult us in advance if planning to use CFC substitute detergent.

#### <Drying after washing>

Dry after washing so that the detergent is not left over. If drying is insufficient, the detergent is left over on the element surface, and the insulation resistance is measured to be lowered. Dry enough so as not to leave detergent.

### 3.1. Washing of chip type

- Since the chip type capacitor does not have a coating, components of flux or detergent left over on the element at the time of washing may be activated and invade into the inside of the capacitor, and adverse effects may be caused. Observe the following cautions.
- In the case of washing, use flux and cream solder with halogen content of 0.1wt.% or less when mounting.
- In the case of ultrasonic washing, note that peeling of protective film, electrode separation due to resonance, or characteristic deterioration may occur depending on the detergent used or ultrasonic output. Check carefully beforehand.
- When using a CFC substitute detergent, with the washing method of spraying detergent (rinsing water) to the substrate at high pressure, the protective film on the element surface may be peeled off due to the water pressure. Check carefully beforehand.

### 3.2. Washing of leaded type

The film capacitor varies significantly in the effect of washing depending on the structure and material, and generally it is less affected by CFC or alcohol derivative washing solvent, and is likely to be affected by highly polar solvent.

The lead type film capacitor is coated with an epoxy resin excellent in chemical resistance, and is hardly affected by detergent, but it is recommended to be washed for short duration.

Applicability of detergents in film capacitors is listed for reference.

< List of applicability of detergents >

Solvent		Washing condition	Chip type	Lead type	Box type	
					ECQUL	
Solvent	Alcohol	Ethanol Ultrasonic washing or immersion washing for 5 min				
		Isopropyl alcohol (IPA) Ultrasonic washing or immersion washing for 5 min				
	Silicon	FRW-17 Ultrasonic washing for 5 min, 60 FRW-1N Ultrasonic washing for 5 min, 60 FRW-100 Steam drying for 1 min, 100				
	Halogen	Asahi Clean AK-225AES Ultrasonic washing or immersion washing for 5 min				
		HCFC141b-MS Ultrasonic washing or immersion washing for 5 min				
	Petroleum hydrocarbon	P3 Cold Cleaner 225S Ultrasonic washing for 5 min 60      IPA ultrasonic rinsing for 5 min at ordinary temperature      hot air drying for 5 min, 40				
		Toluene Ultrasonic washing or immersion washing for 5 min	×			
Water	Terpene	Terpene Cleaner EC-7 Spray washing for 5 min at ordinary temperature      purified water spraying for 5 min, 50      hot air drying for 5 min, 80	×			
	Purified water	Ultrasonic washing for 5 min 60 wind-free drying for 5 min, 85	×			
	Surface active agent	Clean Through 750H Ultrasonic washing for 5 min, 60      purified water ultrasonic washing for 5 min, 60      hot air drying for 5 min, 85	×			
		Clean Through 750L Ultrasonic washing for 5 min, 60      purified water ultrasonic washing for 5 min, 60      hot air drying for 5 min, 85	×			
		Clean Through 710M Ultrasonic washing for 5 min, 60      purified water ultrasonic washing for 5 min, 60      hot air drying for 5 min, 85	×			
		Clean Through LC-841 Ultrasonic washing for 5 min, 60      purified water ultrasonic washing for 5 min, 60      hot air drying for 5 min, 85	×			
		Ultrasonic washing for 5 min, 60      purified water ultrasonic washing for 5 min, 60      hot air drying for 5 min, 85	×			
		Shower washing for 1 min, 60      purified water ultrasonic washing for 5 min, 60      hot air drying for 5 min, 85	×			
: Washing enabled			x : Washing disabled			
			: Not confirmed			

< Wash-free flux >

Wash-free	Low residue flux	ULF-500VS			
	Inactivated flux	AM-173			

Washing disabled (x mark) detergent should be avoided because the appearance may be impaired, the characteristic may be deteriorated, and the reliability cannot be guaranteed