

Industries

Solutions

Services

Software

Products

Partners

Support

About Us



-Search-

Entire Site

Search Results

Evaluate

- FAQ's

Design a Solution

- Part Drawings
- PDF-Pre-Terminat ...

How to Buy

- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Product On-Line Catalog > Search Results >

Current refinements (click Material to remove) Search Tips @ ☑ Text Search: 'F912D3-NM1Y'

Your search criteria matched only one product, shown below

F912D3-NM1Y



Fan-Out Cords — Singlemode 9/125µm (OS1)

- Pass all TIA/EIA-568-C.3 performance requirements
- 100% factory inspected end face geometry in compliance with Telcordia GR-326-CORE, Issue 3
- Typical insertion loss per connection: 0.25dB
- UPC polished (55dB minimum Return Loss)
- Pigtailed (open) end allows quick high performance field fusion splice during installation to provide the lowest installed cost
- 900µm tight-buffered fibers break out to terminated colored buffers for quick and easy identification of separate channels for accurate installations
- Factory terminated and 100% tested for insertion loss and return loss
- Insertion loss and return loss data recorded for every singlemode fan-out cord
- Lifetime traceability of test data to a Q.C. number on each fan-out cord
- Highest quality flame retardant fiber ontic cable with tight-buffered coating on each optical fiber.

-11	ignest quality flame retardant fiber optic cable with tignt-buπered coating on each optical fibe
Part Number	F912D3-NM1Y
■ RoHS Compliancy Status	Intended for use in fixed installations which are outside the scope of RoHS
■ Note	F912D3-NM1Y replaces F912D3-NM1
Part Description	SC to pigtail 12-fiber fan-out cord (twelve SC connectors on one end and open on the other end on distribution cable) — 9/125µm.
Product Type	Fan-out Cords
■ Diameter (mm)	$2\text{mm} \times 4.5\text{mm}$
■ Length (m)	1
Fiber Compatibility	9/125µm
Fiber Cable Type	Ribbon Interconnect Cable
■ Fiber Type	Singlemode
Cable Color	Yellow
Cable Type	Duplex
CE Compliant	No
Connector 1 Type	SC Connector
Connector 2 Type	Pigtail
End Configurations	SC to Pigtail
Fiber Count	12
Flammability Rating	Riser (OFNR)
Pricing Description	PC 12-Fiber SM 12SC-Open 9µm 1m
■ Min. Order UOM	PC
Min. Order Qty.	1
■ BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.