Search Results

Evaluate
- Advertisements
- PDF-Highest Perf..
- FAQ's
- Product Bulletins
- PDF-Direct Burial..
- Videos
- WMV-Panduit Comp..

Design a Solution
- Catalog Cut Sheet
- PDF-GCC6X61/01/ ..
- Part Drawings
- DWG-3-D cad for ..
- PDF-Grounding Cr..
- DWG-2-D cad for ..

How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Install & Maintain
- Installation Instructions
- PDF-Direct Burial..

Home > Products Overview > Search Results >

Current refinements (click ☒ to remove) Search Tips

☒ **Text Search: 'GCC6X61/0-1/0'**

Your search criteria matched only one product, shown below

GCC6X61/0-1/0

• Only a single die required to crimp each element, which speeds installation and reduces costs
• Wide range-taking ability and multi-conductor design provide flexibility with a minimum number of parts, allowing for conductor to conductor, conductor to rebar, and conductor to ground rod applications
• Designed for the enhanced crimp process using patent pending technology meets IEEE Std 837™ – 2002
• Slotted design allows quick and easy assembly of conductor to connector using Panduit cable ties, included
• Pre-applied conductive antioxidant compound ensures a high quality mechanical and electrical bond, speeding installation
• Color-coded and marked with Panduit die index numbers for proper crimp die selection
• UL 467 Listed and CSA 22.2 Certified for grounding and bonding suitable for direct burial in earth or concrete when crimped with Panduit or industry standard crimping tools and Panduit dies
• Complies with vibration tests per MIL-STD-202G (METHOD 201A)

Part Number	GCC6X61/01/0
RoHS Compliancy Status	Compliant
Part Description	Grounding cross connector for #6 SOL – 1/0 STR AWG (16– 50mm²) wire size.
CSA Certified	Yes
UL Listed	Yes
CE Compliant	No
Copper Conductor Size Range (B) (mm²)	(16 – 50)
Copper Lightning Conductor Size Range (A)	59.5 kcmil
Ground Rod Size A (In.)	—
Ground Rod Size A (mm)	—
Height- A	1.37 (34.8mm)
Height- B	1.37 (34.8mm)
Length - A	0.94 (23.9mm)
Length - B	0.94 (23.9mm)
Panduit Color Code	Red
Panduit Die Index No.	PG10
Pricing Description	Ground Cross Connector for #6 SOL– 1/0 STR AWG (16- 50mm²)
Rebar Size A (In.)	—
Rebar Size A (mm)	—
Width - A	0.66 (16.8mm)
Width - B	0.66 (16.8mm)
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Copyright © 1995-2011, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy