

- Evaluate
 - FAQ's
- Design a Solution
 - Catalog Cut Sheet
 - PDFHST0.43-Q2Y
 - Part Drawings
 - PDFThick Wall P..
 - Specification Sheets
 - PDFThick Wall P..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

✖ Text Search: 'HST0.8-6-3Y'

HST0.8-6-3Y



- Shrink ratio of 3:1 insulates a wide range of diameters and irregular shapes, which reduces inventory costs
- Cross-linked, UV resistant material improves flame retardancy, chemical, and temperature resistance
- Thick wall product seals and insulates in one step to speed installation
- Meets Mil Spec AMSDTL-23053/15 Class 1

* For red, add 2 to end of part number package suffix (Example HST0.4 -3-Q2).

▪ Part Number	HST0.86-3Y
▪ RoHS Compliancy Status	Compliant
▪ Note	HST0.86-3Y replaces HST0.86-3
▪ Part Description	Thick Wall Heat Shrink provides excellent protection above or below ground level and is suitable for wet locations and direct burial (UL486D)
▪ Material	Highly flame retardant adhesive lined cross-linked polyolefin
▪ Color	Black
▪ CSA Certified	Yes
▪ Military Specification	AMS-DTL-23053/15 Class 1
▪ UL Listed	Yes
▪ UL Recognized	Yes
▪ Length (In.)	6.0
▪ Length (mm)	152.4
▪ Copper Conductor Size Range	#8 AWG – #1/0
▪ Conductor Size Range (mm)	10 – 50
▪ Flammability Rating	VW-1
▪ Max. Connector O.D. (In.)	0.650
▪ Max. Connector O.D. (mm)	16.5
▪ Max. Recovered I.D. (In.)	0.22
▪ Max. Recovered I.D. (mm)	5.6
▪ Min. Cable O.D. (In.)	0.240
▪ Min. Cable O.D. (mm)	6.1
▪ Min. Expanded I.D. (In.)	0.75
▪ Min. Expanded I.D. (mm)	19.1
▪ Nominal Recovered Wall Thickness (In.)	0.09
▪ Nominal Recovered Wall Thickness (mm)	2.3
▪ Pricing Description	Heat Shrink Thick Adhesive, .8"(20.3mm) Dia, Black
▪ Shrink Ratio	3:1
▪ Temperature Range	-67°F – 230°F (-55°C – 110°C)
▪ Type	WET-SHRINK Thick Wall Heat Shrink Adhesive
▪ Min. Order UOM	PC
▪ Min. Order Qty.	3
▪ BOM Qty. (# of Pkgs.)	0
▪ Add to Favorite Product List	e

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.